

ThreatQuotient



Spur Enrichment Action

Version 1.0.1

November 04, 2024

ThreatQuotient

20130 Lakeview Center Plaza Suite 400
Ashburn, VA 20147

 **ThreatQ Supported**

Support

Email: support@threatq.com

Web: support.threatq.com

Phone: 703.574.9893

Contents

Warning and Disclaimer	3
Support	4
Integration Details.....	5
Introduction	6
Prerequisites	7
Installation.....	8
Configuration	9
Actions	12
Spur Enrichment	13
Enriched Data.....	15
Use Case Example.....	16
Known Issues / Limitations	17
Change Log	18

Warning and Disclaimer

ThreatQuotient, Inc. provides this document “as is”, without representation or warranty of any kind, express or implied, including without limitation any warranty concerning the accuracy, adequacy, or completeness of such information contained herein. ThreatQuotient, Inc. does not assume responsibility for the use or inability to use the software product as a result of providing this information.

Copyright © 2024 ThreatQuotient, Inc.

All rights reserved. This document and the software product it describes are licensed for use under a software license agreement. Reproduction or printing of this document is permitted in accordance with the license agreement.

Support

This integration is designated as **ThreatQ Supported**.

Support Email: support@threatq.com

Support Web: <https://support.threatq.com>

Support Phone: 703.574.9893

Integrations/apps/add-ons designated as **ThreatQ Supported** are fully supported by ThreatQuotient's Customer Support team.

ThreatQuotient strives to ensure all ThreatQ Supported integrations will work with the current version of ThreatQuotient software at the time of initial publishing. This applies for both Hosted instance and Non-Hosted instance customers.



ThreatQuotient does not provide support or maintenance for integrations, apps, or add-ons published by any party other than ThreatQuotient, including third-party developers.

Integration Details

ThreatQuotient provides the following details for this integration:

Current Integration Version	1.0.1
-----------------------------	-------

Compatible with ThreatQ Versions	>= 5.14.0
-------------------------------------	-----------

ThreatQ TQO License Required	Yes
---------------------------------	-----

Support Tier	ThreatQ Supported
--------------	-------------------

Introduction

Spur tracks anonymization services so that you can identify when anonymization services are touching your website, application, or network.

The Spur Enrichment Action enables the automatic enrichment of IP Addresses in ThreatQ using Spur's Context API. The API will tell you if the selected IOCs are used by anonymization services, as well as if the tunnels are used by a specific region, or used by a specific threat.

The integration can perform the following action:

- **Spur Enrichment** - utilizes Spur's API to enrich an IP Address with context pertaining to whether the IOC is used for tunnels and/or anonymization.

The action is compatible with the following indicator types:

- IP Address
- IPv6 Address

The action returns enriched IP Address and IPv6 Address type indicators.



This action is intended for use with ThreatQ TDR Orchestrator (TQO). An active TQO license is required for this feature.

Prerequisites

- An active ThreatQ TDR Orchestrator (TQO) license.
- A Spur API Key.
- A data collection containing at least one of the following indicator types:
 - IP Address
 - IPv6 Address

Installation

Perform the following steps to install the integration:



The same steps can be used to upgrade the integration to a new version.

1. Log into <https://marketplace.threatq.com/>.
2. Locate and download the action zip file.
3. Navigate to the integrations management page on your ThreatQ instance.
4. Click on the **Add New Integration** button.
5. Upload the action zip file using one of the following methods:
 - Drag and drop the zip file into the dialog box
 - Select **Click to Browse** to locate the zip file on your local machine



ThreatQ will inform you if the action already exists on the platform and will require user confirmation before proceeding. ThreatQ will also inform you if the new version of the action contains changes to the user configuration. The new user configurations will overwrite the existing ones for the action and will require user confirmation before proceeding.

You will still need to [configure](#) the action.

Configuration



ThreatQuotient does not issue API keys for third-party vendors. Contact the specific vendor to obtain API keys and other integration-related credentials.

To configure the integration:

1. Navigate to your integrations management page in ThreatQ.
2. Select the **Actions** option from the *Category* dropdown (optional).
3. Click on the action entry to open its details page.
4. Enter the following parameters under the **Configuration** tab:



The configurations set on this page will be used as the default settings when inserting this action into a new workflow. Updating the configurations on this page will not update any instances of this action that have already been deployed to a workflow. In that scenario, you must update the action's configurations within the workflow itself.

PARAMETER	DESCRIPTION
Spur Hostname or IP	The hostname or IP address for your Spur instance. The default value is <code>api.spur.us</code> .
API Key	The API Key from the Spur Account
Attribute Filter	<p>Select the pieces of context to ingest into ThreatQ, from Spur. Options include:</p> <ul style="list-style-type: none"> ◦ ASN ◦ AS Organization ◦ Client Behavior (default) ◦ Client Concentration Country Code ◦ Client Concentration City ◦ Client Concentration State ◦ Client Proxy (default) ◦ Client Type (default) ◦ City ◦ Country Code ◦ State ◦ Risk (default) ◦ Service (default) ◦ Tunnel Type (default) ◦ Tunnel Operator (default) ◦ Is Anonymized (default)

PARAMETER	DESCRIPTION
	<ul style="list-style-type: none"> ◦ Infrastructure (default)
Indicator Filter	Select the indicators to ingest into ThreatQ, from Spur. Options include: <ul style="list-style-type: none"> ◦ Tunnel Entry IPs ◦ Tunnel Exit IPs (default)
Inherit Attributes to Entry/Exit Tunnels	Enable this to inherit enrichment attributes from the original indicator to the tunnel indicators. This parameter is disabled by default.
Only Ingest Enrichment for IPs with Risks / Threats	Enable this to only ingest enrichment for IPs when they are deemed risky or have threats. This option is enabled by default.
Only Ingest Enrichment for IPs from Selected Services (Optional)	Enter a line-separated list of services to filter on. If left blank, IPs from all services will be ingested.
Objects Per Run	The max number of objects per run to send to this action. The default value is 1000.
Disable Proxies	Enable this option if the action should not honor proxies set in the ThreatQ UI.
Enable SSL Verification	Enable or Disable Host SSL certificate verification.

< Spur Enrichment



Uninstall

Additional Information

Integration Type: Action

Version:

Action ID: 1

Accepted Data Types:

☒ Indicators

IP Address

IPv6 Address

Configuration

Authentication

Spur Hostname or IP

The hostname or IP address for your Spur instance

API Key

Enter your Spur API key to authenticate.

Enrichment Filtering

Attribute Filter

Select the pieces of context to ingest into ThreatQ, from Spur.

- ☐ ASN
- ☐ AS Organization
- ☒ Client Behavior
- ☐ Client Concentration Country Code
- ☐ Client Concentration City
- ☐ Client Concentration State
- ☒ Client Proxy
- ☒ Client Type
- ☒ Infrastructure
- ☐ City
- ☒ Country Code
- ☐ State

5. Review any additional settings, make any changes if needed, and click on **Save**.

Actions

The integration performs the following action:

ACTION	DESCRIPTION	OBJECT TYPE	OBJECT SUBTYPE
Spur Enrichment	Fetches contextual information from the Spur API.	Indicator	IP Address, IPv6 Address

Spur Enrichment

The Spur Enrichment action will use Spur's API to enrich an IP Address with context pertaining to whether the IOC is used for tunnels and/or anonymization. As well as how the tunnel is typically used by threats.

GET <https://api.spur.us/v2/context/{{ ip }}>

Sample Response:

```
{
  "as": {
    "number": 30083,
    "organization": "AS-30083-GO-DADDY-COM-LLC"
  },
  "client": {
    "behaviors": ["TOR_PROXY_USER"],
    "concentration": {
      "city": "Weldon Spring",
      "country": "US",
      "density": 0.202,
      "geohash": "9yz",
      "skew": 45,
      "state": "Missouri"
    },
    "count": 14,
    "countries": 1,
    "proxies": ["LUMINATI_PROXY", "SHIFTER_PROXY"],
    "spread": 4941431,
    "types": ["MOBILE", "DESKTOP"]
  },
  "infrastructure": "DATACENTER",
  "ip": "148.72.164.186",
  "location": {
    "city": "St Louis",
    "country": "US",
    "state": "Missouri"
  },
  "risks": ["WEB_SCRAPING", "TUNNEL"],
  "services": ["IPSEC", "OPENVPN"],
  "tunnels": [
    {
      "anonymous": true,
      "entries": ["148.72.164.179"],
      "exits": ["148.72.164.177"],
      "operator": "NORD_VPN",
      "type": "VPN"
    }
  ]
}
```

ThreatQuotient provides the following default mapping for this action:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.as.number	Indicator.Attribute	ASN	N/A	30083	N/A
.as.organization	Indicator.Attribute	AS Organization	N/A	AS-30083-GO-DADDY-COM-LLC	N/A
.client.behaviors[]	Indicator.Attribute	Client Behavior	N/A	TOR_PROXY_USER	N/A
.client.concentration.city	Indicator.Attribute	Client Concentration City	N/A	Weldon Spring	N/A
.client.concentration.country	Indicator.Attribute	Client Concentration Country Code	N/A	US	N/A
.client.concentration.state	Indicator.Attribute	Client Concentration State	N/A	Missouri	N/A
.client.proxies[]	Indicator.Attribute	Client Proxy	N/A	SHIFTER_PROXY	N/A
.client.types[]	Indicator.Attribute	Client Type	N/A	DESKTOP	N/A
.infrastructure	Indicator.Attribute	Infrastructure	N/A	DATACENTER	N/A
.location.city	Indicator.Attribute	City	N/A	St Louis	N/A
.location.country	Indicator.Attribute	Country Code	N/A	US	N/A
.location.state	Indicator.Attribute	State	N/A	Missouri	N/A
.risks[]	Indicator.Attribute	Risk	N/A	WEB_SCRAPING	N/A
.services[]	Indicator.Attribute	Service	N/A	IPSEC	N/A
.tunnels[].operator	Indicator.Attribute	Tunnel Operator	N/A	NORD_VPN	N/A
.tunnels[].type	Indicator.Attribute	Tunnel Type	N/A	VPN	N/A
.tunnels[].entries[]	Indicator.Value	IP Address	N/A	N/A	N/A
.tunnels[].exits[]	Indicator.Value	IP Address	N/A	N/A	N/A
.tunnels[].anonymous	Indicator.Attribute	Is Anonymized	N/A	True	N/A
N/A	Indicator.Attribute	Node Type	N/A	Entry	Entry if the IP is in .tunnels[].entries[]. Exit if the IP is in .tunnels[].exits[]

Enriched Data



Object counts and action runtime are supplied as generalities only - objects returned by a provider can differ based on credential configurations and action runtime may vary based on system resources and load.

METRIC	RESULT
Run Time	2 minutes
Indicators	225
Indicator Attributes	782

Use Case Example

1. A Threat Analyst wants to identify when anonymized services (VPNs and Proxies) are contacting the network infrastructure and take action when the activity is a known threat.
2. The Threat Analyst creates a collection of Indicators that have the type IP Address or IPv6 Address.
3. The Threat Analyst adds the Spur Enrichment action to a Workflow.
4. The Threat Analyst configures the action with the desired parameters, and enables the Workflow.
5. The action will enrich the indicators with information that indicates if they are used by anonymization services.

Known Issues / Limitations

- When the action is run on a unnormalized IPv6 Address ,a new indicator with the normalized value will be created and enriched. The original indicator will not be enriched.

Change Log

- **Version 1.0.1**
 - Added the following configurations parameters:
 - **Spur Hostname or IP** - allows you to specify the hostname or IP of your Spur instance.
 - **Disable Proxies** - enable this option if the action should not honor proxies set in the ThreatQ UI.
 - **Enable SSL Verification** - enable or Disable Host SSL certificate verification.
- **Version 1.0.0**
 - Initial release