

# ThreatQuotient



## Digital Shadows Intelligence CDF Guide

Version 1.2.0

June 06, 2022

**ThreatQuotient**

11400 Commerce Park Dr., Suite 200  
Reston, VA 20191

 ThreatQ Supported

### Support

Email: [support@threatq.com](mailto:support@threatq.com)

Web: [support.threatq.com](https://support.threatq.com)

Phone: 703.574.9893

# Contents

Support .....	4
Versioning.....	5
Introduction .....	6
Installation.....	7
Configuration .....	8
<b>ThreatQ Mapping .....</b>	<b>11</b>
Digital Shadows Intelligence Threats .....	11
{ID} .....	13
IOCs.....	17
Table Mapping.....	18
Digital Shadows Intelligence Incidents.....	20
{ID} .....	22
IOCs.....	24
Table Mapping.....	25
<b>Average Feed Run.....</b>	<b>28</b>
Digital Shadows Intelligence Threats .....	28
Digital Shadows Intelligence Incidents.....	29
<b>Known Issues / Limitations .....</b>	<b>30</b>
<b>Change Log.....</b>	<b>31</b>

# Warning and Disclaimer

ThreatQuotient, Inc. provides this document “as is”, without representation or warranty of any kind, express or implied, including without limitation any warranty concerning the accuracy, adequacy, or completeness of such information contained herein. ThreatQuotient, Inc. does not assume responsibility for the use or inability to use the software product as a result of providing this information.

Copyright © 2022 ThreatQuotient, Inc.

All rights reserved. This document and the software product it describes are licensed for use under a software license agreement. Reproduction or printing of this document is permitted in accordance with the license agreement.

# Support

This integration is designated as **ThreatQ Supported**.

**Support Email:** [support@threatq.com](mailto:support@threatq.com)

**Support Web:** <https://support.threatq.com>

**Support Phone:** 703.574.9893

Integrations/apps/add-ons designated as **ThreatQ Supported** are fully supported by ThreatQuotient's Customer Support team.

ThreatQuotient strives to ensure all ThreatQ Supported integrations will work with the current version of ThreatQuotient software at the time of initial publishing. This applies for both Hosted instance and Non-Hosted instance customers.



ThreatQuotient does not provide support or maintenance for integrations, apps, or add-ons published by any party other than ThreatQuotient, including third-party developers.

# Versioning

- Current integration version: 1.2.0
- Compatible with ThreatQ versions  $\geq$  4.28.0

# Introduction

The Digital Shadows Intelligence CDF ingests threat intelligence data from Digital Shadows Intelligence Threats and Public Intelligence Incidents feeds.

The CDF provides the following feeds:

- **Digital Shadows Intelligence Threats** - ingests adversaries, malware, events, campaigns, indicators, tools, and TTPs from Digital Shadows.
- **Digital Shadows Intelligence Incidents** - ingests public intelligence incidents from Digital Shadows.

The CDF ingests the following system objects:

- Adversaries
- Incidents
  - Incident Attributes
- Indicators
  - Indicator Attributes
- Malware
  - Malware Attributes
- TTPs

# Installation

Perform the following steps to install the integration:



The same steps can be used to upgrade the integration to a new version.

1. Log into <https://marketplace.threatq.com/>.
2. Locate and download the integration file.
3. Navigate to the integrations management page on your ThreatQ instance.
4. Click on the **Add New Integration** button.
5. Upload the integration file using one of the following methods:
  - Drag and drop the file into the dialog box
  - Select **Click to Browse** to locate the integration file on your local machine



ThreatQ will inform you if the feed already exists on the platform and will require user confirmation before proceeding. ThreatQ will also inform you if the new version of the feed contains changes to the user configuration. The new user configurations will overwrite the existing ones for the feed and will require user confirmation before proceeding.

6. If prompted, select the individual feeds to install and click **Install**. The feed will be added to the integrations page.

You will still need to [configure and then enable the feed](#).

# Configuration



ThreatQuotient does not issue API keys for third-party vendors. Contact the specific vendor to obtain API keys and other integration-related credentials.

To configure the integration:

1. Navigate to your integrations management page in ThreatQ.
2. Select the **Commercial** option from the *Category* dropdown (optional).



If you are installing the integration for the first time, it will be located under the **Disabled** tab.

3. Click on the integration to open its details page.
4. Enter the following parameters under the **Configuration** tab:

## Required Parameters for both Feeds

PARAMETER	DESCRIPTION
API ID	Your API ID provided by Digital Shadows.
API Key	Your API key provided by Digital Shadows.
Threat Types	Select one or more threat types to be ingested. Options include: <ul style="list-style-type: none"><li>◦ Actors (default)</li><li>◦ Campaigns (default)</li><li>◦ Events (default)</li><li>◦ Tools (default)</li><li>◦ TTPs (default)</li></ul>
Save CVE Data As	Select the ThreatQ object types to be created from CVE data. Options include: <ul style="list-style-type: none"><li>◦ Vulnerabilities</li></ul>



PARAMETER	DESCRIPTION
	<ul style="list-style-type: none"><li>◦ Indicators (default)</li></ul>
<b>Ingest Events as Incident Objects</b>	If enabled, the integration will ingest fetched incidents as ThreatQ incident objects. If not enabled, fetched incidents will be ingested as Event objects. This parameters is enabled by default.

### Additional Parameters for Digital Shadows Intelligence Threats

PARAMETER	DESCRIPTION
<b>Threat Levels</b>	Select one or more threat levels to be ingested. Options include: <ul style="list-style-type: none"><li>◦ Very High (default)</li><li>◦ High (default)</li><li>◦ Medium (default)</li><li>◦ Low</li><li>◦ Very Low</li><li>◦ Unassessed</li></ul>
<b>Relevant to Organization Only</b>	If enabled, the integration will only ingest threats that are flagged as relevant to your organization. If not enabled, the integration will ingest all threats.

### Additional Parameter for Digital Shadows Intelligence Incidents


PARAMETER	DESCRIPTION
<b>Severities</b>	Select one or more severities to be ingested. Options include: <ul style="list-style-type: none"><li>◦ Very High (default)</li><li>◦ High (default)</li></ul>

## PARAMETER

## DESCRIPTION

- Medium (default)
- Low
- Very Low
- None

< Digital Shadows Intelligence Threats



Disabled ☒ Enabled

Uninstall

Additional Information

Integration Type: Feed

Version: 1.2.0

Configuration

Activity Log

API ID

API ID

API Key

API Key

Threat Types

One or more threat types to be ingested.

☒ Actors

☒ Campaigns

☒ Events

☒ Tools

☒ TTPs

Threat Levels

One or more threat levels to be ingested.

☒ Very High

☒ High

☒ Medium

☐ Low

☐ Very Low

☒ Unassessed

Save CVE Data As

ThreatQuotient maps CVE data as CVE indicators by default.

☐ Vulnerabilities

☒ Indicators

5. Review any additional settings, make any changes if needed, and click on **Save**.
6. Click on the toggle switch, located above the *Additional Information* section, to enable it.

# ThreatQ Mapping

ThreatQuotient provides section provides feed urls, sample responses, and default ThreatQ mapping.

## Digital Shadows Intelligence Threats

The Digital Shadows Intelligence Threats feed ingests adversaries, malware, events, campaigns, indicators, tools, and TTPs from Digital Shadows.

POST <https://portal-digitalshadows.com/api/intel-threats/find>

### Sample Response:

```
{
  "content": [
    {
      "id": 4049,
      "primaryTag": {
        "id": 5642
      },
      "type": "SPECIFIC_TTP",
      "threatLevel": {
        "type": "MEDIUM"
      },
      "activityLevel": "RECENT",
      "overview": "The TrickBot banking trojan was first reported publicly on 15 Oct 2016 by the security firm Fidelis. The malware was developed to enable its users to harvest online banking credentials from customers of banks targeted in the malware configuration file. This is achieved through the use of webinjects which are inserted into an infected user's browser. The objective of banking trojans is generally unauthorized access into customer bank accounts to facilitate fraudulent transactions, but TrickBot has also targeted users of services such as Salesforce and crypto-currency entities. [[trickbot configs 2017-11-07][https://pastebin.com/ZnU7tuvB]]. [[TrickBot expands targeting][https://f5.com/labs/articles/threat-intelligence/malware/trickbot-expands-global-targets-beyond-banks-and-payment-processors-to-crms]]. On 13 Oct 2016, the first samples of TrickBot were detected, which included a webinject module; the configuration files of these samples showed that customers of four Australian banks and one Canadian bank had been affected. [[TrickBot: We missed you, Dyre][http://www.threatgeek.com/2016/10/trickbot-the-dyre-connection.html]] Subsequent reporting also identified the targeting of bank customers in the United Kingdom, New Zealand and Germany. [[Aggressive launch of TrickBot][https://securityintelligence.com/an-aggressive-launch-trickbot-trojan-rises-with-redirection-attacks-in-the-uk]] Further to this, the following locations were known to have been affected by TrickBot activity: [[TrickBot targeting developments][https://www.digitalshadows.com/blog-and-research/coming-to-a-country-near-you-the-rapid-development-of-the-trickbot-trojan/]]\r\n\r\n- Argentina (see incident $ {incident:23821757})\r\n- Australia\r\n- Canada\r\n- Chile (see incident ${incident:23821757})\r\n- Colombia (see incident ${incident:23821757})\r\n- Denmark (see incident ${incident:19594419})\r\n- Finland (see incident $ {incident:19594419})\r\n- France\r\n- Germany\r\n- Isle of Man\r\n- Ireland\r\n- India\r\n- Israel (see incident $ {incident:19594419})\r\n- Italy (see incident ${incident:19594419})\r\n- Malaysia \r\n- New Zealand\r\n- Netherlands [[TrickBot config from 11 Apr 2017][https://pastebin.com/SedUcQ2X]]\r\n- Norway (see incident $ {incident:19594419})\r\n- Peru (see incident ${incident:23821757})\r\n- Singapore\r\n- Sweden (see incident $ {incident:19594419})\r\n- Switzerland (see incident ${incident:19594419})\r\n- United Kingdom\r\n- United States\r\n\r\nTrickBot has been distributed via the use of spam emails containing malicious Microsoft Office attachments (see incident ${incident:13475074}), malicious JavaScript files (see incident ${incident:13657353}) and the RIG exploit kit (see incident ${incident:13475074}). On 09 Jun 2017, distribution was reported via the Necurs
```

botnet; between 0900 and 1800 BST on 07 Jun 2017, 9.6 million emails were detected by Forcepoint (see incident \${incident:19594419}). Distribution of TrickBot via Necurs has been a consistent trend since mid-2017. Despite the number of reported distribution methods, the number of infections associated with TrickBot and any amount of losses resulting from this activity was not known. \r\n\r\nFollowing distribution, TrickBot was downloaded and installed via the use of a downloader called TrickLoader, reportedly crypted via a cryptor also used for Vawtrak, Pushdo and Cutwail malware. The downloader analysed system bit information before decoding appropriate resources. TrickBot has contained modules enumerating an infected system's information, and to exfiltrate data to attackers, as well as a webinject configuration stored in an injectDLL module. \r\n\r\nTrickBot used at least two methods to propagate between machines and network shares on a local network. On 26 Jul 2017, individual researchers discovered a sample of TrickBot that used the EternalBlue exploit for a server message block (SMB) vulnerability (CVE-2017-0144) to propagate between machines (see incident \${incident:21129761}). Furthermore, in Sep 2017, a TrickBot sample reportedly implemented a new module named "WormShare" that used Windows API calls to create copies of the malware on network shares. [[TrickBot adds WormShare module][<http://www.vkremez.com/2017/09/lets-learn-reversing-trickbot-banking.html>]] \r\n\r\nTrickBot was reportedly very similar to the Dyre banking trojan in relation to the functions and activities it carried out. However, the "code styles" of issuing command to the bot were reportedly different, Trickbot engaged TaskScheduler, with Dyre deploying direct communication. Furthermore, there was reportedly more use of the C++ programming language in TrickBot than Dyre. Overall, Fidelis assessed with "strong confidence" that there was a link between Dyre and TrickBot, but that there had been a considerable amount of new development invested into TrickBot. Fidelis assessed with a "moderate confidence" that one or more of the original Dyre developers had been involved in the development of TrickBot [[TrickBot: We missed you, Dyre][<http://www.threatgeek.com/2016/10/trickbot-the-dyre-connection.html>]] While the similarities presented by Fidelis were probably true, we had not confirmed the links between TrickBot and Dyre at the time of writing. In Feb 2016, reporting on arrests of individuals in Russia in Nov 2015, coupled with a cessation of Dyre activity, led to speculation that the group behind the Dyre banking trojan had been arrested and the operations disrupted (see incident \${incident:6471059}). \r\n\r\nSince its inception TrickBot has undergone a considerable level of development, with the incorporation of webinject modules and configuration for targeting banks and other services. Additionally, TrickBot reportedly targeted private and business banks, as well as eight building societies. [[TrickBot targeting private banks][<https://securityintelligence.com/trickbot-is-hand-picking-private-banks-for-targets-with-redirection-attacks-in-tow/>]] Based on our analysis of the configuration files for TrickBot, Australian banks were the most commonly included in these configuration files, showing a realistic possibility customers of these banks were predominantly affected. It was assessed that at least in the near future TrickBot would continue to expand its targeting within these locations and likely target further locations in future (see incident \${incident:14305506}). ",

```
    "lastActive": "2020-04-06T23:00:00.000Z",
    "overviewTags": [],
    "imageThumbnailId": "378e90ec-b4d3-41cc-b071-4bbdf545733b"
  }
],
"currentPage": {
  "offset": 0,
  "size": 12
},
"total": 1
}
```

## {ID}

GET <https://portal-digitalshadows.com/api/intel-threats/{ID}>

### Sample Response:

```
{
  "id": 4049,
  "primaryTag": {
    "id": 5642,
    "name": "TrickBot",
    "type": "SPECIFIC_TTP"
  },
  "type": "SPECIFIC_TTP",
  "threatLevel": {
    "type": "MEDIUM",
    "reason": "The TrickBot banking trojan has targeted customers from a large number of banks, financial services and online platforms. The rapid development and global reach of Trickbot indicates that developers are well resourced. The group behind the malware is likely to have access to mule infrastructure to facilitate cash out and money laundering operations. The multiple delivery methods used by its operators showed they were willing to invest resources into its widespread distribution. As a result of these indicators, TrickBot was assessed to represent a Medium threat level at the time of writing."
  },
  "activityLevel": "RECENT",
  "summary": "TrickBot is a banking trojan that was first detected in Sep 2016 and since that time had been developed to incorporate the targeting of multiple geographies and online services. The malware was developed to gain unauthorized access to customer bank accounts to facilitate fraudulent transactions, but also targeted users of online services such as Salesforce and cryptocurrency services. The malware was reportedly delivered via spam emails containing malicious attachments, including those distributed by the Necurs botnet, and via the RIG exploit kit. In some cases, TrickBot used an exploit called EternalBlue (affects CVE-2017-0144) or Windows API calls to propagate in a local network. The functions and activities of TrickBot are reportedly very similar to the Dyre banking trojan, and it was assessed by researchers to be linked to this trojan, including that at least one of the developers of Dyre was involved in the development of TrickBot. The widespread targeting and rapid, continuing development meant that the malware represented a Medium threat level at the time of writing.",
  "overview": "The TrickBot banking trojan was first reported publicly on 15 Oct 2016 by the security firm Fidelis. The malware was developed to enable its users to harvest online banking credentials from customers of banks targeted in the malware configuration file. This is achieved through the use of webinjects which are inserted into an infected user's browser. The objective of banking trojans is generally unauthorized access into customer bank accounts to facilitate fraudulent transactions, but TrickBot has also targeted users of services such as Salesforce and cryptocurrency entities. [[trickbot configs 2017-11-07][https://pastebin.com/ZnU7tuvB]]. [[TrickBot expands targeting][https://f5.com/labs/articles/threat-intelligence/malware/trickbot-expands-global-targets-beyond-banks-and-payment-processors-to-crms]]. On 13 Oct 2016, the first samples of TrickBot were detected, which included a webinject module; the configuration files of these samples showed that customers of four Australian banks and one Canadian bank had been affected. [[TrickBot: We missed you, Dyre][http://www.threatgeek.com/2016/10/trickbot-the-dyre-connection.html]] Subsequent reporting also identified the targeting of bank customers in the United Kingdom, New Zealand and Germany. [[Aggressive launch of TrickBot][https://securityintelligence.com/an-aggressive-launch-trickbot-trojan-rises-with-redirection-attacks-in-the-uk]] Further to this, the following locations were known to have been affected by TrickBot activity: [[TrickBot targeting developments][https://www.digitalshadows.com/blog-and-research/coming-to-a-country-near-you-the-rapid-development-of-the-trickbot-trojan/]]\r\n\r\n- Argentina (see incident ${incident:23821757})\r\n- Australia\r\n- Canada\r\n- Chile (see incident ${incident:23821757})\r\n- Colombia (see incident ${incident:23821757})\r\n- Denmark (see incident ${incident:19594419})\r\n- Finland (see incident ${incident:19594419})\r\n- France\r\n- Germany\r\n- Isle of Man\r\n- Ireland\r\n- India\r\n- Israel (see incident ${incident:19594419})\r\n- Italy (see incident ${incident:19594419})\r\n- Malaysia \r\n- New Zealand\r\n- Netherlands [[TrickBot config from 11 Apr 2017][https://pastebin.com/SedUcQ2X]]\r\n- Norway (see incident ${incident:19594419})\r\n- Peru (see incident ${incident:23821757})\r\n- Singapore\r\n- Sweden (see incident ${incident:19594419})\r\n- Switzerland (see incident ${incident:19594419})\r\n- United Kingdom\r\n- United States\r\n\r\nTrickBot has been distributed via the use of spam emails containing malicious Microsoft Office
```

attachments (see incident \${incident:13475074}), malicious JavaScript files (see incident \${incident:13657353}) and the RIG exploit kit (see incident \${incident:13475074}). On 09 Jun 2017, distribution was reported via the Necurs botnet; between 0900 and 1800 BST on 07 Jun 2017, 9.6 million emails were detected by Forcepoint (see incident \${incident:19594419}). Distribution of TrickBot via Necurs has been a consistent trend since mid-2017. Despite the number of reported distribution methods, the number of infections associated with TrickBot and any amount of losses resulting from this activity was not known. \r\n\r\nFollowing distribution, TrickBot was downloaded and installed via the use of a downloader called TrickLoader, reportedly crypted via a cryptor also used for Vawtrak, Pushdo and Cutwail malware. The downloader analysed system bit information before decoding appropriate resources. TrickBot has contained modules enumerating an infected system's information, and to exfiltrate data to attackers, as well as a webinject configuration stored in an injectDLL module. \r\n\r\nTrickBot used at least two methods to propagate between machines and network shares on a local network. On 26 Jul 2017, individual researchers discovered a sample of TrickBot that used the EternalBlue exploit for a server message block (SMB) vulnerability (CVE-2017-0144) to propagate between machines (see incident \${incident:21129761}). Furthermore, in Sep 2017, a TrickBot sample reportedly implemented a new module named "WormShare" that used Windows API calls to create copies of the malware on network shares.[[TrickBot adds WormShare module][<http://www.vkremez.com/2017/09/lets-learn-reversing-trickbot-banking.html>]]\r\n\r\nTrickBot was reportedly very similar to the Dyre banking trojan in relation to the functions and activities it carried out. However, the "code styles" of issuing command to the bot were reportedly different, Trickbot engaged TaskScheduler, with Dyre deploying direct communication. Furthermore, there was reportedly more use of the C++ programming language in TrickBot than Dyre. Overall, Fidelis assessed with "strong confidence" that there was a link between Dyre and TrickBot, but that there had been a considerable amount of new development invested into TrickBot. Fidelis assessed with a "moderate confidence" that one or more of the original Dyre developers had been involved in the development of TrickBot[[TrickBot: We missed you, Dyre][<http://www.threatgeek.com/2016/10/trickbot-the-dyre-connection.html>]] While the similarities presented by Fidelis were probably true, we had not confirmed the links between TrickBot and Dyre at the time of writing. In Feb 2016, reporting on arrests of individuals in Russia in Nov 2015, coupled with a cessation of Dyre activity, led to speculation that the group behind the Dyre banking trojan had been arrested and the operations disrupted (see incident \${incident:6471059}). \r\n\r\n\r\nSince its inception TrickBot has undergone a considerable level of development, with the incorporation of webinject modules and configuration for targeting banks and other services. Additionally, TrickBot reportedly targeted private and business banks, as well as eight building societies.[[TrickBot targeting private banks][<https://securityintelligence.com/trickbot-is-hand-picking-private-banks-for-targets-with-redirection-attacks-in-tow/>]] Based on our analysis of the configuration files for TrickBot, Australian banks were the most commonly included in these configuration files, showing a realistic possibility customers of these banks were predominantly affected. It was assessed that at least in the near future TrickBot would continue to expand its targeting within these locations and likely target further locations in future (see incident \${incident:14305506}). ",

```
"lastActive": "2020-04-06T23:00:00.000Z",
"overviewTags": [],
"imageId": "9a155fe2-a2c1-4561-a4a7-1c59098e975e",
"imageThumbnailId": "378e90ec-b4d3-41cc-b071-4bbdf545733b",
"tacticTags": [
  {
    "id": 2694,
    "name": "Credential Harvesters",
    "type": "GENERAL_TTP",
    "parent": {
      "id": 2682
    }
  }
],
"motivationTags": [
  {
    "id": 443,
    "name": "Financial or Economic",
    "type": "MOTIVATION"
  }
],
"primaryLanguageTags": [
  {
    "id": 467,
    "name": "English",
    "type": "LANGUAGE"
  }
],
```

```
"sourceGeographyTags": [],
"actorTypeTags": [
  {
    "id": 1112,
    "name": "eCrime Actor - Malware Developer",
    "type": "ACTOR_TYPE"
  }
],
"targetGeographyTags": [
  {
    "id": 855,
    "name": "Canada",
    "type": "TARGET_GEOGRAPHY",
    "parent": {
      "id": 990
    }
  }
],
"targetSectorTags": [
  {
    "id": 1080,
    "name": "Banks",
    "type": "TARGET_SECTORS"
  }
],
"intendedEffectTags": [
  {
    "id": 401,
    "name": "Theft - Credential Theft",
    "type": "INTENDED_EFFECTS"
  }
],
"impactEffectTags": [
  {
    "id": 428,
    "name": "Financial Loss",
    "type": "IMPACT_EFFECTS"
  }
],
"associatedActorTags": [
  {
    "id": 7732,
    "name": "Lazarus Group",
    "type": "ACTOR"
  }
],
"associatedCampaignTags": [],
"associatedEvents": [
  {
    "id": 5148,
    "primaryTag": {
      "id": 15482,
      "name": "COVID-19 pandemic",
      "type": "EVENT"
    },
    "type": "EVENT",
    "closedSource": false,
    "threatLevel": {
      "type": "HIGH"
    },
    "activityLevel": "INACTIVE",
```

```
        "event": {
          "recurring": false
        }
      },
    ],
    "latestIncident": {
      "id": 61058206,
      "scope": "GLOBAL"
    },
    "sites": [],
    "detailLevel": "FULL",
    "indicatorOfCompromiseCount": 355,
    "aptReports": [
      {
        "id": "39c68dd0-f9ed-472f-b46b-4d9153ae5442"
      },
      {
        "id": "109c2b6b-3c2e-4e6c-bd58-16d38c4c1dba"
      }
    ],
    "mitigation": "Mitigations against malware such as this should be focused on deploying a defense-in-depth strategy to protect against initial infection and for post infection. A strategy for defense should use a blend of technical and non-technical controls in order to be most effective, some of the components that should be used include:\r\n\r\n• Security awareness training, staff should be educated on the risks associated with clicking on links and attachments within emails.\r\n\r\n• Filter email and attachments, it may be wise to block executable file types including those compressed within archives such as zip and RAR.\r\n\r\n• Advanced malware detection devices should be deployed to monitor incoming email streams as well as subsequent downloads.\r\n\r\n• End point controls should be implemented on the end users' computers to help limit opening of malicious file attachments and to catch malware installations/executions.\r\n\r\n• Apply post-infection controls such as firewall policies, web proxies, and log monitoring to identify abnormalities.\r\n\r\n• Keep antivirus databases, operating systems and applications up to date.\r\n",
    "toolTags": [],
    "cveNumberTags": []
  }
}
```



## IOCs

GET <https://portal-digitalshadows.com/api/intel-threats/{ID}/iocs>

### Sample JSON Response:

```
{
  "content": [
    {
      "id": 5666,
      "type": "MD5",
      "value": "0804499dba4090c439e580f5693660e0",
      "aptReport": {
        "id": "109c2b6b-3c2e-4e6c-bd58-16d38c4c1dba"
      }
    },
  ]
}
```

## Table Mapping

The mapping below maps the JSON responses above from the Digital Shadows Intelligence Threats Feed.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.content[].primaryTag.name	Adversary.Value	N/A	N/A	N/A	Ingested when .content[].primaryTag.type is ACTOR
.content[].primaryTag.name	Event.Title/ Incident.Value	Incident	N/A	N/A	Ingested when .content[].primaryTag.type is EVENT. ThreatQ object type varies depending on the <b>Ingest Events as Incident Objects</b> setting
.content[].primaryTag.name	Malware.Value	N/A	N/A	Trickbot	Ingested when .content[].primaryTag.type is SPECIFIC_TTP
.content[].primaryTag.name	Tool.Value	N/A	N/A	N/A	Ingested when .content[].primaryTag.type is TOOLS
.content[].primaryTag.name	Campaign.Value	N/A	N/A	N/A	Ingested when .content[].primaryTag.type is CAMPAIGN
.content[].lastActive	Event.HappenedAt/ Incident.OccurredAt	N/A	N/A	N/A	N/A
.content[].threatLevel.type	Object.Attribute	Threat Level	N/A	MEDIUM	N/A
.content[].threatLevel.reason	Object.Attribute	Threat Level Reason	N/A	N/A	N/A
.content[].activityLevel	Object.Attribute	Activity Level	N/A	RECENT	N/A
.content[].recurring	Object.Attribute	Recurring Event	N/A	True	N/A
.content[].actorTypeTags[].name	Object.Attribute	Actor Type	N/A	Hacker	N/A
.content[].impactEffectTags[].name	Object.Attribute	Impact Effect	N/A	Financial Loss	N/A
.content[].intendedEffectTags[].name	Object.Attribute	Intended Effect	N/A	Theft - Credential Theft	N/A
.content[].primaryLanguageTags[].name	Object.Attribute	Language	N/A	English	N/A
.content[].sourceGeographyTags[].name	Object.Attribute	Source Geography	N/A	Canada	N/A
.content[].specifiedTargetTags[].name	Object.Attribute	Specified Target	N/A	N/A	N/A
.content[].targetGeographyTags[].name	Object.Attribute	Target Geography	N/A	Canada	N/A
.content[].targetSectorTags[].name	Object.Attribute	Target Sector	N/A	Banks	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.content[].overview	Object.Attribute	Overview	N/A	The TrickBot banking trojan was first reported publicly on 15 Oct 2016...	N/A
.content[].knownMembersDescription	Object.Attribute	Known Members Description	N/A	N/A	N/A
.content[].mitigation	Object.Attribute	Recommended Action	N/A	Mitigations against malware such as this should...	N/A
.content[].tacticDescription	Object.Attribute	Tactic Description	N/A	N/A	N/A
.content[].id	Object.Attribute	Digital Shadows Portal Link	N/A	N/A	Formatted with portal URL
.content[].value	Indicator.Value	.content[].type	N/A	N/A	iocs are from the supplemental feed
.content[].cveNumberTags[].name	Indicator.Value/ Vulnerability.Value	CVE for Indicator, N/A for Vulnerability	N/A	N/A	ThreatQ object types vary depending on the <b>Save CVE Data as</b> settings
.content[].associatedActorTags[].name	Adversary.Name	N/A	N/A	N/A	Above attributes do not apply
.content[].tacticTags[].name	TTP.Value	N/A	N/A	Credential Harvesters	Filtered down to only CATEGORY_TTP and GENERAL_TTP types
.content[].tacticTags[].name	Malware.Value	N/A	N/A	N/A	Filtered down to only SPECIFIC_TTP types
.content[].associatedCampaignTags[].name	Campaign.Value	Campaign	N/A	N/A	Above attributes do not apply
.content[].toolTags[].name	Tool.Value	Tool	N/A	N/A	N/A
.content[].associatedEvents[].primaryTag.name	Related Event.value	N/A	N/A	COVID-19 pandemic	N/A
.content[].associatedEvents[].threatLevel.type	Incident.Attribute	Threat Level	N/A	HIGH	N/A
.content[].associatedEvents[].activityLevel	Incident.Attribute	Activity Level	N/A	INACTIVE	N/A
.content[].associatedEvents[].event.recurring	Incident.Attribute	Recurring	N/A	FALSE	N/A

# Digital Shadows Intelligence Incidents

The Digital Shadows Intelligence Incidents feed ingests public intelligence incidents from Digital Shadows.

GET <https://portal-digitalshadows.com/api/intel-incidents/find> Sample JSON response:

## Sample Response:

```
{
  "content": [
    {
      "id": 61133184,
      "scope": "GLOBAL",
      "type": "CYBER_THREAT",
      "severity": "LOW",
      "title": "xHelper Android malware remains active",
      "published": "2020-04-14T08:38:57.835Z",
      "closedSource": false,
      "summary": "Cyber-security researchers reported that the xHelper Android malware variants has remained highly active in 2020.",
      "modified": "2020-04-14T08:38:57.842Z",
      "occurred": "2020-04-06T23:00:00.000Z",
      "verified": "2020-04-14T08:38:20.851Z",
      "tags": [
        {
          "id": 8710,
          "name": "Mobile malware",
          "type": "GENERAL_TTP"
        },
        {
          "id": 170,
          "name": "Industry News",
          "type": "GENERAL"
        },
        {
          "id": 9532,
          "name": "Android",
          "type": "SPECIFIED_TARGETS"
        },
        {
          "id": 2701,
          "name": "Remote Access Trojan",
          "type": "GENERAL_TTP"
        },
        {
          "id": 3181,
          "name": "Secondary source",
          "type": "GENERAL"
        },
        {
          "id": 1903,
          "name": "Social Engineering",
          "type": "GENERAL_TTP"
        }
      ]
    }
  ],
}
```

```
"version": 5,
"score": 0,
"entitySummary": {
  "source": "https://threatpost.com/xhelper-russian-nesting-doll-android-malware/154519/",
  "summaryText": "Ultimately delivering the Triada payload, xHelper goes to great lengths to become virtually
indestructible once installed on a smartphone.",
  "domain": "threatpost.com",
  "sourceDate": "2020-04-06T23:00:00.000Z",
  "type": "WEB_PAGE",
  "contentRemoved": false
},
"description": "On 07 Apr 2020 cyber-security researchers reported that the xHelper Android malware variant
(see incident 57711200) has remained highly active in 2020. This has included operations where it has been used to
deliver the \"Triada\" trojan. \r\n\r\nThe infection chain starts by convincing a victim to download a malicious
trojanized app. This has included an operation where xHelper was embedded in an app that masqueraded as a popular
cleaner and speed-up utility for smartphones.\r\n\r\nFurther technical details are available in the additional source
included below. \r\n\r\nSource evaluation: Threat Post is usually reliable; the information is probably true.
\r\n\r\nAdditional source: \r\n- https://securelist.com/unkillable-xhelper-and-a-trojan-matryoshka/96487/",
  "linkedContentIncidents": [],
  "internal": false,
  "restrictedContent": false,
  "indicatorOfCompromiseCount": 18
}
]
```

## {ID}

GET <https://portal-digitalshadows.com/api/intel-incidents/{ID}>

### Sample Response:

```
{
  "id": 61133184,
  "scope": "GLOBAL",
  "type": "CYBER_THREAT",
  "severity": "LOW",
  "title": "xHelper Android malware remains active",
  "published": "2020-04-14T08:38:57.835Z",
  "closedSource": false,
  "summary": "Cyber-security researchers reported that the xHelper Android malware variants has remained highly active in 2020.",
  "modified": "2020-04-14T08:38:57.842Z",
  "occurred": "2020-04-06T23:00:00.000Z",
  "verified": "2020-04-14T08:38:20.851Z",
  "tags": [
    {
      "id": 8710,
      "name": "Mobile malware",
      "type": "GENERAL_TTP"
    },
    {
      "id": 170,
      "name": "Industry News",
      "type": "GENERAL"
    },
    {
      "id": 9532,
      "name": "Android",
      "type": "SPECIFIED_TARGETS"
    },
    {
      "id": 2701,
      "name": "Remote Access Trojan",
      "type": "GENERAL_TTP"
    },
    {
      "id": 3181,
      "name": "Secondary source",
      "type": "GENERAL"
    },
    {
      "id": 1903,
      "name": "Social Engineering",
      "type": "GENERAL_TTP"
    }
  ],
  "version": 5,
  "score": 0,
  "entitySummary": {
    "source": "https://threatpost.com/xhelper-russian-nesting-doll-android-malware/154519/",
    "summaryText": "Ultimately delivering the Triada payload, xHelper goes to great lengths to become virtually indestructible once installed on a smartphone."
  }
}
```

```
"domain": "threatpost.com",
"sourceDate": "2020-04-06T23:00:00.000Z",
"type": "WEB_PAGE",
"contentRemoved": false
},
"description": "On 07 Apr 2020 cyber-security researchers reported that the xHelper Android malware variant (see incident 57711200) has remained highly active in 2020. This has included operations where it has been used to deliver the \"Triada\" trojan. \r\n\r\nThe infection chain starts by convincing a victim to download a malicious trojanized app. This has included an operation where xHelper was embedded in an app that masqueraded as a popular cleaner and speed-up utility for smartphones.\r\n\r\nFurther technical details are available in the additional source included below. \r\n\r\nSource evaluation: Threat Post is usually reliable; the information is probably true. \r\n\r\nAdditional source: \r\n- https://securelist.com/unkillable-xhelper-and-a-trojan-matryoshka/96487/",
"linkedContentIncidents": [],
"internal": false,
"restrictedContent": false,
"indicatorOfCompromiseCount": 18
}
```

## IOCs

GET <https://portal-digitalshadows.com/api/intel-threats/{ID}/iocs>

### Sample Response:

```
{
  "content": [
    {
      "id": 18306,
      "type": "IP",
      "value": "172.104.215.170",
      "source": "https://securelist.com/unkillable-xhelper-and-a-trojan-matryoshka/96487/",
      "lastUpdated": "2020-04-07T00:00:00.000Z"
    }
  ]
}
```



## Table Mapping

The mapping below maps the JSON responses above from the `Digital Shadows Intelligence Incidents Feed`.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.content[].title	Event.Title/ Incident.Value	Incident	.content[].published	xHelper Android malware remains active	N/A
.content[].occurred	Event.HappenedAt/ Incident.OccurredAt	N/A	N/A	N/A	ThreatQ object type varies depending on user field settings
.content[].tags[].name	TTP.Value	N/A	.content[].published	N/A	Filtered down to only CATEGORY_TTP and GENERAL_TTP types
.content[].tags[].name	Malware.Value	N/A	.content[].published	N/A	Filtered down to only SPECIFIC_TTP types
.content[].tags[].name	Adversary.Name	N/A	.content[].published	N/A	Filtered down to only ACTOR types
.content[].tags[].name	Indicator.Value/ Vulnerability.Value	CVE for Indicator, N/A for Vulnerability	.content[].published	N/A	Filtered down to only CVE_NUMBER types. ThreatQ object types vary depending on user field settings
.content[].tags[].name	Tool.Value	N/A	.content[].published	N/A	Filtered down to only TOOLS types
.content[].tags[].name	Object.Attribute	.content[].tags.type	.content[].published	N/A	See table below for attribute type mapping
.content[].severity	Event.Attribute	Severity	.content[].published	LOW	N/A
.content[].type	Event.Attribute	Type	.content[].published	CYBER_THREAT	N/A
.content[].subType	Event.Attribute	Subtype	.content[].published	N/A	N/A
.content[].summary	Event.Attribute	Summary	.content[].published	Cyber-security researchers reported that the xHelper Android malware variants have remained highly active in 2020.	N/A
.content[].scope	Event.Attribute	Scope	.content[].published	GLOBAL	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.content[].verified	Event.Attribute	Verified At	.content[].published	2020-04-14T09:31:33.991Z	N/A
.content[].internal	Event.Attribute	Is Internal	.content[].published	N/A	N/A
.content[].version	Event.Attribute	Version	.content[].published	5	N/A
.content[].entitySummary. summaryText	Event.Attribute	Entity Summary	.content[].published	Ultimately delivering the Triada payload, xHelper goes to great lengths to become virtually indestructible once installed on a smartphone.	N/A
.content[].entitySummary. source	Event.Attribute	Entity Source	.content[].published	<a href="https://threatpost.com/xhelper-russian-nesting-doll-android-malware/154519">https://threatpost.com/xhelper-russian-nesting-doll-android-malware/154519</a>	N/A
.content[].entitySummary. domain	Event.Attribute	Entity Domain	.content[].published	threatpost.com	N/A
.content[].entitySummary. sourceDate	Event.Attribute	Entity Source Date	.content[].published	2020-04-06T23:00:00.000Z	N/A
.content[].entitySummary. screenshotThumbnailId	Event.Attribute	Entity Screenshot ID	.content[].published	N/A	N/A
.content[].entitySummary. type	Event.Attribute	Entity Type	.content[].published	WEB_PAGE	N/A
.content[].entitySummary. fullText	Event.Attribute	Entity Text	.content[].published	N/A	N/A
.content[].entitySummary. contentRemoved	Event.Attribute	Entity Content Removed	.content[].published	false	N/A
.content[].alerted	Event.Attribute	Alerted At	.content[].published	N/A	N/A
.content[].mitigation	Event.Attribute	Mitigation	.content[].published	N/A	N/A
.content[].impactDescription	Event.Attribute	Impact Description	.content[].published	N/A	N/A
.content[].takedownRequestCount	Event.Attribute	Takedown Request Count	.content[].published	N/A	N/A
.content[].restrictedContent	Event.Attribute	Restricted Content	.content[].published	false	N/A
.content[].score	Event.Attribute	Score	.content[].published	N/A	N/A

The values in `.content[].tags` which are ingested as attributes are as follows:

DIGITAL SHADOWS TYPE	THREATQ ATTRIBUTE KEY
TARGET_GEOGRAPHY	Target Geography
INTENDED_EFFECTS	Intended Effect
SOURCE_GEOGRAPHY	Source Geography
GENERAL	Tag
DATA_BREACH	Breached Data
IMPACT_EFFECTS	Impact Effect
EVENT_TYPE	Event Type

---

DIGITAL SHADOWS TYPE	THREATQ ATTRIBUTE KEY
ACTOR_TYPE	Actor Type
LANGUAGE	Language
TARGET_SECTORS	Target Sector
SPECIFIED_TARGETS	Specified Target

# Average Feed Run



Object counts and Feed runtime are supplied as generalities only - objects returned by a provider can differ based on credential configurations and Feed runtime may vary based on system resources and load.

## Digital Shadows Intelligence Threats

Metrics provided using the default user field settings.

METRIC	RESULT
Run Time	1 minute
Adversaries	3
Incidents	2
Incident Attributes	90
Indicators	35
Indicator Attributes	5
Malware	10
Malware Attributes	90
TTPs	20

# Digital Shadows Intelligence Incidents

Metrics provided using default user field settings.

METRIC	RESULT
Run Time	< 1 minute
Incidents	20
Incident Attributes	550
Indicators	10
Malware	1
TTPs	10

# Known Issues / Limitations

- the Digital Shadows Intelligence Incidents feed *does not* ingest related events or incidents.
- This integration's feeds only supports a Start Date for manual runs and will use the current time as the End Date.

# Change Log

- **Version 1.2.0**
  - Fixed an issue where `.indicatorOfCompromiseCount == 0` or `1` resulted in an `Error` creating objects from threat data error message in the activity log.
- **Version 1.1.0**
  - Fixed a pagination issue.
  - Updated the Digital Shadows Intelligence Threat Feed endpoint to address missing information in the feed.
- **Version 1.0.0**
  - Initial release