

# ThreatQuotient



## Netscout AED Connector User Guide

**Version 1.0.0**

October 18, 2023

**ThreatQuotient**

20130 Lakeview Center Plaza Suite 400  
Ashburn, VA 20147

 **ThreatQ Supported**

### **Support**

Email: [support@threatq.com](mailto:support@threatq.com)

Web: [support.threatq.com](https://support.threatq.com)

Phone: 703.574.9893

# Contents

<b>Warning and Disclaimer .....</b>	<b>3</b>
<b>Support .....</b>	<b>4</b>
<b>Integration Details.....</b>	<b>5</b>
<b>Introduction .....</b>	<b>6</b>
<b>Prerequisites .....</b>	<b>7</b>
Time Zone .....	7
Integration Dependencies .....	8
<b>Installation.....</b>	<b>9</b>
Creating a Python 3.6 Virtual Environment .....	9
Installing the Connector.....	10
<b>Configuration .....</b>	<b>12</b>
<b>Usage.....</b>	<b>14</b>
Command Line Arguments.....	14
CRON .....	16
<b>Change Log .....</b>	<b>17</b>

# Warning and Disclaimer

ThreatQuotient, Inc. provides this document “as is”, without representation or warranty of any kind, express or implied, including without limitation any warranty concerning the accuracy, adequacy, or completeness of such information contained herein. ThreatQuotient, Inc. does not assume responsibility for the use or inability to use the software product as a result of providing this information.

Copyright © 2023 ThreatQuotient, Inc.

All rights reserved. This document and the software product it describes are licensed for use under a software license agreement. Reproduction or printing of this document is permitted in accordance with the license agreement.

# Support

This integration is designated as **ThreatQ Supported**.

**Support Email:** [support@threatq.com](mailto:support@threatq.com)

**Support Web:** <https://support.threatq.com>

**Support Phone:** 703.574.9893

Integrations/apps/add-ons designated as **ThreatQ Supported** are fully supported by ThreatQuotient's Customer Support team.

ThreatQuotient strives to ensure all ThreatQ Supported integrations will work with the current version of ThreatQuotient software at the time of initial publishing. This applies for both Hosted instance and Non-Hosted instance customers.



ThreatQuotient does not provide support or maintenance for integrations, apps, or add-ons published by any party other than ThreatQuotient, including third-party developers.

---

# Integration Details

ThreatQuotient provides the following details for this integration:

Current Integration Version	1.0.1
-----------------------------	-------

Compatible with ThreatQ Versions	>= 4.45.0
-------------------------------------	-----------

Python Version	3.6
----------------	-----

Support Tier	ThreatQ Supported
--------------	-------------------

# Introduction

The Netscout Arbor Edge Defense (AED) connector ingests alerts from Netscout into ThreatQ.

---

# Prerequisites

Review the following requirements before attempting to install the connector.

## Time Zone

You should ensure all ThreatQ devices are set to the correct time, time zone, and date (UTC is recommended), and using a clock source available to all.

To identify which time zone is closest to your present location, use the `timedatectl` command with the `list-timezones` command line option.

For example, enter the following command to list all available time zones in Europe:

```
timedatectl list-timezones | grep Europe
Europe/Amsterdam
Europe/Athens
Europe/Belgrade
Europe/Berlin
```


Enter the following command, as root, to change the time zone to UTC:

```
timedatectl set-timezone UTC
```

## Integration Dependencies

 The integration must be installed in a python 3.6 environment.

The following is a list of required dependencies for the integration. These dependencies are downloaded and installed during the installation process. If you are an Air Gapped Data Sync (AGDS) user, or run an instance that cannot connect to network services outside of your infrastructure, you will need to download and install these dependencies separately as the integration will not be able to download them during the install process.

 Items listed in bold are pinned to a specific version. In these cases, you should download the version specified to ensure proper function of the integration.

DEPENDENCY	VERSION	NOTES
<b>more-itertools</b>	<b>5.0.0</b>	<b>Pinned</b>
<b>six</b>	<b>1.13.0</b>	<b>Pinned</b>
<b>stix2</b>	<b>2.0.2</b>	<b>Pinned</b>
<b>stix2_patterns</b>	<b>2.0.0</b>	<b>Pinned</b>
<b>taxii2-client</b>	<b>2.2.2</b>	<b>Pinned</b>
threatqcc	>=1.3.1	N/A
threatqsdk	>=1.8.0	N/A
wheel	N/A	N/A
pytz	N/A	N/A
tzlocal	N/A	N/A
dateparser	N/A	N/A



---

# Installation

The following provides you with steps on installing a Python 3 Virtual Environment and installing the connector.


## Creating a Python 3.6 Virtual Environment

Run the following commands to create the virtual environment:

```
mkdir /opt/tqvenv/  
sudo yum install -y python36 python36-libs python36-devel python36-pip  
python3.6 -m venv /opt/tqvenv/<environment_name>  
source /opt/tqvenv/<environment_name>/bin/activate  
pip install --upgrade pip  
pip install threatqsdk threatqcc setuptools==59.6.0
```

Proceed to [Installing the Connector](#).

## Installing the Connector

 **Upgrading Users** - Review the [Change Log](#) for updates to configuration parameters before updating. If there are changes to the configuration file (new/removed parameters), you must first delete the previous version's configuration file before proceeding with the install steps listed below. Failure to delete the previous configuration file will result in the connector failing.

1. Navigate to the ThreatQ Marketplace and download the .whl file for the integration.
2. Activate the virtual environment if you haven't already:

```
source /opt/tqenv/<environment_name>/bin/activate
```

3. Transfer the whl file to the /tmp directory on your ThreatQ instance.
4. Install the connector on your ThreatQ instance:

```
pip install /tmp/tq_conn_netscout_aed-<version>-py3-none-any.whl
```



A driver called tq-conn-netscout-aed will be installed. After installing, a script stub will appear in /opt/tqenv/<environment\_name>/bin/tq-conn-netscout-aed.

5. Once the application has been installed, a directory structure must be created for all configuration, logs and files, using the `mkdir -p` command. Use the commands below to create the required directories:

```
mkdir -p /etc/tq_labs/  
mkdir -p /var/log/tq_labs/
```

6. Perform an initial run using the following command:

```
/opt/tqenv/<environment_name>/bin/tq-conn-netscout-aed -ll /var/log/  
tq_labs/ -c /etc/tq_labs/ -v3
```

7. Enter the following parameters when prompted:

PARAMETER	DESCRIPTION
ThreatQ Host	This is the host of the ThreatQ instance, either the IP Address or Hostname as resolvable by ThreatQ.
ThreatQ Client ID	This is the OAuth id that can be found at Settings Gear → User Management → API details within the user's details.
ThreatQ Username	This is the Email Address of the user in the ThreatQ System for integrations.
ThreatQ Password	The password for the above ThreatQ account.
Status	This is the default status for objects that are created by this Integration.

### Example Output

```
/opt/tqvenv/<environment_name>/bin/tq-conn-netscout-aed -ll /var/log/
tq_labs/ -c /etc/tq_labs/ -v3
ThreatQ Host: <ThreatQ Host IP or Hostname>
ThreatQ Client ID: <ClientID>
ThreatQ Username: <EMAIL ADDRESS>
ThreatQ Password: <PASSWORD>
Status: Review
Connector configured. Set information in UI
```

You will still need to [configure and then enable the connector](#).

# Configuration



ThreatQuotient does not issue API keys for third-party vendors. Contact the specific vendor to obtain API keys and other integration-related credentials.

To configure the integration:

1. Navigate to your integrations management page in ThreatQ.
2. Select the **Labs** option from the *Category* dropdown (optional).
3. Click on the integration entry to open its details page.
4. Enter the following parameters under the **Configuration** tab:

PARAMETER	DESCRIPTION
Hostname	The hostname or IP address of the Arbor Edge Defense appliance.
API Token	The API Token from Arbor Edge Defense.
STIX Client Username	The username configured in the Arbor EdgeDefense appliance configured to ingest threat intelligence.
STIX Client Password	The password associated with the username provided above.
ThreatQ Data Collection	The name of the data collection in ThreatQ in which to pull data from.
AES STIX Collection Name	The collection name in AED that is configured to store threat intelligence.
Relationship Depth	This is how many relationship "levels" you want to fetch. (Max of 3)
Default Indicator Labels	The default labels given to the indicator, assuming no matching label is present in the attributes.
Default Threat Actor Labels	The default labels given to a related threat actor, assuming no matching label is present in the attributes.

PARAMETER	DESCRIPTION
Default Malware Labels	The default labels given to a related malware, assuming no matching label is present in the attributes.
Default Tool Labels	The default labels given to a related tool, assuming no matching label is present in the attributes.
Default Report Labels	The default labels given to a related report, assuming no matching label is present in the attributes.
Alert Severity	The severity of alerts ti import from AED.
Query Keywords	A comma-delimited "," list of search strings to filter alerts on.

5. Review any additional settings, make any changes if needed, and click on **Save**.
6. Click on the toggle switch, located above the *Additional Information* section, to enable it.

# Usage

Use the following command to execute the driver:

```
/opt/tqenv/<environment_name>/bin/tq-conn-netscout-aed -v3 -ll /var/log/tq_labs/ -c /etc/tq_labs/
```

## Command Line Arguments

This connector supports the following custom command line arguments:

ARGUMENT	DESCRIPTION
<code>-h, --help</code>	Shows this help message and exits.
<code>-ll LOGLOCATION, --loglocation LOGLOCATION</code>	Sets the logging location for the connector. The location should exist and be writable by the current. A special value of 'stdout' means to log to the console (this happens by default).
<code>-c CONFIG, --config CONFIG</code>	This is the location of the configuration file for the connector. This location must be readable and writable by the current user. If no config file path is given, the current directory will be used. This file is also where some information from each run of the connector may be put (last run time, private oauth, etc.)
<code>-d, --disable-ssl</code>	This argument will allow you to disable SSL verification when making requests to the AED appliance.
<code>-i, --import</code>	This argument will allow you to run the import-only portion of the application. This will import events from AED into ThreatQ.
<code>-e, --export</code>	This argument will allow you to run the export-only portion of the application. This will export threat intelligence from ThreatQ to AED.
<code>-n, --name (connector name)</code>	This argument allows you to install the connector with a custom name. This argument is mainly used when you want to install multiple instances of the connector. For instance, if you have multiple saved

---

**ARGUMENT****DESCRIPTION**

---

searches that you want exported. You can simply setup anew instance of this connector with a new name, for a new saved search.

## CRON

Automatic CRON configuration has been removed from this script. To run this script on a recurring basis, use CRON or some other jobs scheduler. The argument in the CRON script must specify the config and log locations.

Add an entry to your Linux crontab to execute the connector at a recurring interval. Depending on how quickly you need updates, this can be run multiple times a day (no more than once an hour) or a few times a week.

In the example below, the command will execute the connector every two hours.

1. Log into your ThreatQ host via a CLI terminal session.
2. Enter the following command:

```
crontab -e
```

This will enable the editing of the crontab, using vi. Depending on how often you wish the cronjob to run, you will need to adjust the time to suit the environment.

3. Enter the commands below:

### Every 2 Hours Example

```
0 */2 * * * /opt/tqenv/<environment_name>/bin/tq-conn-netscout-aed -  
c /etc/tq_labs/ -ll /var/log/tq_labs/ -v3
```

4. Save and exit CRON.



---

# Change Log

- **Version 1.0.1**
  - Added support for library dependencies to prevent possible initial run errors.
  - Added python 3 support.
- **Version 1.0.0**
  - Initial release