

ThreatQuotient

A Securonix Company



Recorded Future CDF

Version 2.15.3

August 10, 2026

ThreatQuotient

20130 Lakeview Center Plaza Suite 400
Ashburn, VA 20147



ThreatQ Supported

Support

Email: tq-support@securonix.com

Web: <https://ts.securonix.com>

Phone: 703.574.9893

Contents

Warning and Disclaimer	4
Support	5
Integration Details	6
Introduction	7
Prerequisites	9
Compromised Account and Entities Custom Object	10
ThreatQ V6 Steps	10
ThreatQ v5 Steps	11
Installation	13
Configuration	14
Recorded Future Domain Risk List Parameters	14
Recorded Future Vulnerability Risk List Parameters	19
Recorded Future Hash Risk List Parameters	23
Recorded Future IP Risk List Parameters	26
Recorded Future URL Risk List Parameters	30
Recorded Future Analyst Note Parameters	33
Recorded Future Alerts Parameters	37
Recorded Future Playbook Alerts Parameters	40
Recorded Future Fusion Files Parameters	43
Recorded Future Detection Rules Parameters	47
ThreatQ Mapping	49
Recorded Future Domain Risk List	49
Recorded Future IP Risk List	52
Recorded Future URL Risk List	53
Recorded Future Vulnerability Risk List	55
Recorded Future Hash Risk List	57
Recorded Future Analyst Note	59
Entities Mapping	62
Recorded Future Alerts	64
Related Indicator Type Mapping	71
Event Attributes Mapping	72
Recorded Future Playbook Alerts	74
Recorded Future - Get Playbook Alerts by Category (Supplemental)	78
Domain Abuse	78
Third Party Risk	82
Cyber Vulnerability	85
Code Repo Leakage	88
Recorded Future Fusion Files	91
Command and Control IPs	91
Known TOR IPs	94
Active RAT C2 IPs	95
Fast Flux IPs	97
Default IP Risklist Location Malware	98
Default Hash / Domain CSV	100
Dynamic DNS IPs	103
Potentially Undetectable Malware	104
Weaponized Domains	106

Exploits in the Wild Hashes	108
Recorded Future Detection Rules	109
Entities Attributes Mapping	112
Average Feed Run	115
Recorded Future Domain Risk List	115
Recorded Future IP Risk List	115
Recorded Future URL Risk List	115
Recorded Future Vulnerability Risk	116
Recorded Future Hash Risk List	116
Recorded Future Analyst Note	116
Recorded Future Alerts.....	117
Recorded Future Playbook Alerts	119
Recorded Future Fusion Files.....	120
Recorded Future Detection Rules	120
Known Issues / Limitations	122
Change Log	123

Warning and Disclaimer

ThreatQuotient, Inc. provides this document "as is", without representation or warranty of any kind, express or implied, including without limitation any warranty concerning the accuracy, adequacy, or completeness of such information contained herein.

ThreatQuotient, Inc. does not assume responsibility for the use or inability to use the software product as a result of providing this information.

Copyright © 2026 ThreatQuotient, Inc.

All rights reserved. This document and the software product it describes are licensed for use under a software license agreement. Reproduction or printing of this document is permitted in accordance with the license agreement.

Support

This integration is designated as **ThreatQ Supported**.

Support Email: tq-support@securonix.com

Support Web: <https://ts.securonix.com>

Support Phone: 703.574.9893

Integrations/apps/add-ons designated as **ThreatQ Supported** are fully supported by ThreatQuotient's Customer Support team.

ThreatQuotient strives to ensure all ThreatQ Supported integrations will work with the current version of ThreatQuotient software at the time of initial publishing. This applies for both Hosted instance and Non-Hosted instance customers.



ThreatQuotient does not provide support or maintenance for integrations, apps, or add-ons published by any party other than ThreatQuotient, including third-party developers.

Integration Details

ThreatQuotient provides the following details for this integration:

Current Integration Version	2.15.3
Compatible with ThreatQ Versions	>= 5.6.0
Support Tier	ThreatQ Supported

Introduction

The Recorded Future CDF ingests threat intelligence data from the following feeds published by the *Recorded Future* vendor:

- **Recorded Future Domain Risk List** - retrieves information in the form of a CSV list where the first token is risk data and the last token containing the supporting context.
- **Recorded Future IP Risk List** - retrieves IP Addresses from the provider.
- **Recorded Future URL Risk List** - retrieves URLs from the provider.
- **Recorded Future Vulnerability Risk List** - retrieves CVEs from the provider.
- **Recorded Future Hash Risk List** - retrieves Hashes from the provider.
- **Recorded Future Analyst Note** - retrieves Reports, Indicators, and Attack Patterns from the provider.
- **Recorded Future Alerts** - retrieves Alerts from the provider as ThreatQ Events and all the related Indicators, Malware, Adversaries, Attack Patterns and Vulnerabilities, Image files and Entity objects.
 - **Recorded Future Alerts Details (Supplemental)** - retrieves related data for each of the ingested events retrieved from the Alert endpoint.
- **Recorded Future Playbook Alerts** - retrieves a list of alerts filtered by the values provided in the configuration section.
 - **Recorded Future - Get Playbook Alerts (Supplemental)** - retrieves related data for each of the ingested events retrieved from the Alert endpoint.
- **Recorded Future Fusion Files** - ingests threat intelligence information from the user selected Fusion feeds.
- **Recorded Future Detection Rules** - ingests Recorded Future detection rules (i.e. YARA, Snort, or Sigma) into ThreatQ as Signatures.

The integration ingests the following system objects:

- Adversaries
 - Adversary Tags
- Assets
 - Asset Attributes
- Attack Patterns
 - Attack Pattern Attributes

-
- Compromised Account (custom object)
 - Entities (custom object)
 - Files
 - Identities
 - Indicators
 - Indicator Attributes and Tags
 - Malware
 - Malware Attributes
 - Reports
 - Report Attributes
 - Signatures
 - Signature Attributes
 - Vulnerabilities
 - Vulnerability Attributes and Tabs

Prerequisites

The following is required to install and run the integration:

- Recorded Future API Key.
- [Compromised Account and Entity custom objects](#) installed on your ThreatQ instance.
- MITRE ATT&CK attack patterns must have already been ingested by a previous run of the MITRE ATT&CK feeds in order for MITRE ATT&CK attack patterns ingested by the Analyst Note feed to be created. MITRE ATT&CK attack patterns are ingested from the following feeds:
 - MITRE Enterprise ATT&CK
 - MITRE Mobile ATT&CK
 - MITRE PRE-ATT&CK

Compromised Account and Entities Custom Object

The integration requires the Compromised Account and Entity custom objects which must be installed prior to installing the CDF. Use the steps provided to install the custom objects.

 When installing the custom objects, be aware that any in-progress feed runs will be cancelled, and the API will be in maintenance mode.

ThreatQ V6 Steps

Use the following steps to install the custom object in ThreatQ v6:

1. Download the integration bundle from the ThreatQ Marketplace.
2. Unzip the bundle and locate the custom object files.



The custom object files will typically consist of a JSON definition file, install.sh script, and a images folder containing the svg icons.

3. SSH into your ThreatQ instance.
4. Set your install pathway environment variable. This command will retrieve the install pathway from your configuration file and set it as variable for use during this installation process.

```
INSTALL_CONF="/etc/threatq/platform/install.conf"

if [ -f "$INSTALL_CONF" ]; then source "$INSTALL_CONF"
fi

MISC_DIR="${INSTALL_BASE_PATH:-/var/lib/threatq}/misc"
```

5. Navigate to the tmp folder using the environment variable:

```
cd $MISC_DIR
```

6. Upload the custom object files, including the images folder.

The directory structure should resemble the following:

- install.sh

- <custom_object_name>.json
- images (directory)
 - <custom_object_name>.svg

7. Run the following command:

```
kubectl exec -it deployment/api-schedule-run -n threatq --  
sh /var/lib/threatq/misc/install.sh /var/lib/threatq/misc
```



The installation script will automatically put the application into maintenance mode, move the files to their required directories, install the custom object, update permissions, bring the application out of maintenance mode, and restart dynamo.

8. Delete the install.sh, definition json file, and images directory from step 6 after the object has been installed as these files are no longer needed.

ThreatQ v5 Steps

Use the following steps to install the custom object in ThreatQ v5:

1. Download the integration zip file from the ThreatQ Marketplace and unzip its contents.
2. SSH into your ThreatQ instance.
3. Navigate to tmp directory:

```
cd /tmp/
```

4. Create a new directory:

```
mkdir recorded_future_cdf
```

5. Upload the **recorded_future.json** and **install.sh** script into this new directory.
6. Create a new directory called **images** within the recorded_future_cdf directory.

```
mkdir images
```

7. Upload the account and entity svg files.
8. Navigate to the **/tmp/recorded_future_cdf**.

The directory should resemble the following:

- tmp
 - **recorded_future_cdf**
 - **recorded_future.json**
 - **install.sh**
 - **images**
 - **account.svg**
 - **entity.svg**

9. Run the following command to ensure that you have the proper permissions to install the custom object:

```
chmod +x install.sh
```

10. Run the following command:

```
sudo ./install.sh
```



You must be in the directory level that houses the install.sh and json files when running this command.

The installation script will automatically put the application into maintenance mode, move the files to their required directories, install the custom object, update permissions, bring the application out of maintenance mode, and restart dynamo.

11. Remove the temporary directory, after the custom object has been installed, as the files are no longer needed:

```
rm -rf recorded_future_cdf
```

Installation

 The integration requires the installation of the Compromised Account and Entity custom objects. See the [Prerequisites](#) chapter for more details. These custom objects must be installed prior to installing the CDF. Attempting to install the CDF prior to installing the custom objects will result in the CDF install process failing.

Perform the following steps to install the integration:

 The same steps can be used to upgrade the integration to a new version.

1. Log into <https://marketplace.threatq.com/>.
2. Locate and download the integration zip file.
3. Extract the contents of the zip and [install the required custom objects](#).
4. Navigate to the integrations management page on your ThreatQ instance.
5. Click on the **Add New Integration** button.
6. Upload the integration yaml file using one of the following methods:
 - Drag and drop the yaml file into the dialog box
 - Select **Click to Browse** to locate the yaml file on your local machine
7. Select the individual feeds to install, when prompted, and click **Install**. The feed will be added to the integrations page.

 ThreatQ will inform you if the feed already exists on the platform and will require user confirmation before proceeding. ThreatQ will also inform you if the new version of the feed contains changes to the user configuration. The new user configurations will overwrite the existing ones for the feed and will require user confirmation before proceeding.

You will still need to [configure and then enable](#) the feed.

Configuration



ThreatQuotient does not issue API keys for third-party vendors. Contact the specific vendor to obtain API keys and other integration-related credentials.

To configure the integration:

1. Navigate to your integrations management page in ThreatQ.
2. Select the **Commercial** option from the *Category* dropdown (optional).



If you are installing the integration for the first time, it will be located under the **Disabled** tab.

3. Click on the integration entry to open its details page.
4. Enter the following parameters under the **Configuration** tab:



All Recorded Future feeds require the Recorded Future API Key. The tables below provide any additional parameters required for specific feeds included with this integration.

Recorded Future Domain Risk List Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Risk Rule Triggered	Optional - Enable this parameter to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected, all the indicators satisfying the rest of the criteria are ingested. Options include:

PARAMETER

DESCRIPTION

- | | |
|---|---|
| <ul style="list-style-type: none"> ◦ Historically Reported by Insikt Group ◦ Historically Reported Botnet Domain ◦ Newly Registered Certificate With Potential for Abuse - DNS Sandwich ◦ Newly Registered Certificate With Potential for Abuse - Typo or Homograph ◦ C&C Nameserver ◦ Historical C&C DNS Name ◦ Historical COVID-19-Related Domain Lure ◦ Recently Resolved to Host of Many DDNS Names ◦ Historically Reported as a Defanged DNS Name ◦ Historically Reported by DHS AIS ◦ Recent Fast Flux DNS Name ◦ Historically Reported Fraudulent Content ◦ Frequently Abused Free DNS Provider ◦ Historically Reported in Threat List ◦ Historically Linked to Cyber Attack ◦ Historically Detected Malware Operation ◦ Historically Suspected Malware Operation | <ul style="list-style-type: none"> ◦ Recently Reported Fraudulent Content ◦ Recently Linked to Cyber Attack ◦ Recently Detected Malware Operation ◦ Recently Suspected Malware Operation ◦ Recent Cryptocurrency Mining Pool ◦ Recently Detected Cryptocurrency Mining Techniques ◦ Recent Phishing Lure: Malicious ◦ Recent Phishing Lure: Suspicious ◦ Recently Detected Phishing Techniques ◦ Recently Suspected Phishing Techniques ◦ Recent Web Filter Avoidance Proxy Domain ◦ Recent Punycode Domain ◦ Recently Referenced by Insikt Group ◦ Recently Reported Spam or Unwanted Content ◦ Recent Suspected C&C DNS Name ◦ Recent Threat Researcher |
|---|---|

PARAMETER

DESCRIPTION

- | | |
|---|---|
| <ul style="list-style-type: none"> ◦ Historically Detected Cryptocurrency Mining Techniques ◦ Blacklisted DNS Name ◦ No Risk Observed ◦ Observed in the Wild by Recorded Future Telemetry ◦ Historical Phishing Lure ◦ Historically Detected Phishing Techniques ◦ Historically Suspected Phishing Techniques ◦ Active Phishing URL ◦ Recorded Future Predictive Risk Model ◦ Historically Detected Web Filter Avoidance Proxy Domain ◦ Historical Punycode Domain ◦ Recently Reported by Insikt Group ◦ Recently Reported Botnet Domain ◦ Recent C&C DNS Name ◦ Recent COVID-19-Related Domain Lure: Malicious ◦ Recent COVID-19-Related Domain Lure: Suspicious ◦ Recently Reported as a Defanged DNS Name ◦ Recently Reported by DHS AIS | <ul style="list-style-type: none"> ◦ Recent Typosquat Similarity - DNS Sandwich ◦ Recent Typosquat Similarity - Typo or Homograph ◦ Recent Ukraine-Related Domain Lure: Malicious ◦ Recent Ukraine-Related Domain Lure: Suspicious ◦ Recently Active Weaponized Domain ◦ Recently Defaced Site ◦ Historically Referenced by Insikt Group ◦ Recently Resolved to Malicious IP ◦ Recently Resolved to Suspicious IP ◦ Recently Resolved to Unusual IP ◦ Recently Resolved to Very Malicious IP ◦ Trending in Recorded Future Analyst Community ◦ Historically Reported Spam or Unwanted Content ◦ Historical Suspected CANDC DNS Name ◦ Historical Threat Researcher ◦ Historical Typosquat Similarity - DNS Sandwich |
|---|---|

PARAMETER	DESCRIPTION
	◦ Historical Typosquat Similarity - Typo or Homograph ◦ Historical Ukraine-Related Domain Lure ◦ Historically Active Weaponized Domain
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>  This parameter is only accessible if you have enabled the Normalize Risk Score parameter.
Filter Out Entries with No New Evidence	Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no

PARAMETER

DESCRIPTION

new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.

< Recorded Future Domain Risk List



Disabled ☐ Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration

Activity Log

Description

This feed ingests Recorded Future Default Domain risk list

Authentication Configuration

API Key

.....



☐ Enable SSL Verification

☒ Disable Proxies

If true, specifies that this feed should not honor any proxies setup in ThreatQuotient

Ingestion Options

Risk Rule Triggered (Optional)

Indicators are added to the default risk list if they trigger any existing Recorded Future risk rule. Enable this option to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected all the indicators satisfying the rest of the criteria are ingested.

☐ Historically Reported by Insikt Group

☐ Historically Reported Botnet Domain

☐ Newly Registered Certificate With Potential for Abuse - DNS Sandwich

☐ Newly Registered Certificate With Potential for Abuse - Typo or Homograph

☐ C&C Nameserver

☐ Historical C&C DNS Name

☐ Historical COVID-19-Related Domain Lure

☐ Recently Resolved to Host of Many DDNS Names

☐ Historically Reported as a Defanged DNS Name

☐ Historically Reported by DHS AIS

☐ Recent Fast Flux DNS Name

☐ Historically Reported Fraudulent Content

Recorded Future Vulnerability Risk List Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Risk Rule Triggered	Optional - Enable this parameter to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected, all the indicators satisfying the rest of the criteria are ingested. Options include: - Historically Reported by Insikt Group - Web Reporting Prior to CVSS Score - Cyber Exploit Signal: Critical - Cyber Exploit Signal: Important - Cyber Exploit Signal: Medium - Historically Exploited in the Wild by Malware - Likely Historical Exploit Development - Linked to Historical Cyber Exploit - NIST Severity: Low - NIST Severity: Medium - Web Reporting Prior to NVD Disclosure - Historical Unverified Proof of Concept Available - Historical Verified Proof of Concept Available - Historical Verified Proof of Concept Available Using Remote Execution - Recently Reported by Insikt Group - Exploit Likely in Active Development - Exploited in the Wild by Recently Active Malware - Recent Unverified Proof of Concept Available

PARAMETER	DESCRIPTION
	◦ Historically Linked to Exploit Kit ◦ Historically Linked to Malware ◦ Historically Linked to Remote Access Trojan ◦ Historically Linked to Ransomware ◦ Linked to Recent Cyber Exploit ◦ Recently Linked to Exploit Kit ◦ Recently Linked to Malware ◦ Recently Linked to Remote Access Trojan ◦ Recently Linked to Ransomware ◦ Exploited in the Wild by Malware ◦ NIST Severity: Critical ◦ NIST Severity: High
	◦ Recent Verified Proof of Concept Available ◦ Recent Verified Proof of Concept Available Using Remote Execution ◦ Recently Referenced by Insikt Group ◦ Recently Linked to Penetration Testing Tools ◦ Historically Referenced by Insikt Group ◦ Historically Linked to Penetration Testing Tools ◦ Vendor Severity: Critical ◦ Vendor Severity: High ◦ Vendor Severity: Low ◦ Vendor Severity: Medium
Save CVE Data As	Select whether to ingest CVEs as Vulnerabilities or Indicators.  The default setting is to ingest Indicators objects.
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.

PARAMETER	DESCRIPTION
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>  This parameter is only accessible if you have enabled the Normalize Risk Score parameter.
Filter Out Entries with No New Evidence	Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.

< Recorded Future Vulnerability Risk List



Disabled ☐ Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration

Activity Log

Description

This feed ingests Recorded Future Default Vulnerability risk list

Authentication Configuration

API Key

☐ Enable SSL Verification

☒ Disable Proxies

If true, specifies that this feed should not honor any proxies setup in ThreatQuotient

Ingestion Options

Risk Rule Triggered (Optional)

Indicators are added to the default risk list if they trigger any existing Recorded Future risk rule. Enable this option to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected all the indicators satisfying the rest of the criteria are ingested.

☐ Historically Reported by Insikt Group

☐ Web Reporting Prior to CVSS Score

☐ Cyber Exploit Signal: Critical

☐ Cyber Exploit Signal: Important

☒ Cyber Exploit Signal: Medium

☐ Historically Exploited in the Wild by Malware

☐ Likely Historical Exploit Development

☐ Linked to Historical Cyber Exploit

☐ Historically Linked to Exploit Kit

☐ Historically Linked to Malware

Recorded Future Hash Risk List Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Risk Rule Triggered	Optional - Enable this parameter to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected, all the indicators satisfying the rest of the criteria are ingested. Options include: - Reported by Insikt Group - Reported by DHS AIS - Historically Reported in Threat List - Linked to Cyber Attack - Linked to Malware - Linked to Attack Vector - Linked to Vulnerability - Malware SSL Certificate Fingerprint - Positive Sandbox Detection on File From Underground Virus Testing Sites - No Risk Observed - Observed in Underground Virus Testing Sites - Observed in the Wild by Recorded Future Telemetry - Positive Malware Verdict - Recently Active Targeting Vulnerabilities in the Wild - Referenced by Insikt Group - Trending in Recorded Future Analyst Community - Suspicious Behavior Detected - Threat Researcher
Ingested Hash Types	Select the type of hashes to be ingested into ThreatQ. Options include

PARAMETER	DESCRIPTION
	◦ MD5 ◦ SHA-1 ◦ SHA-256
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>  This parameter is only accessible if you have enabled the Normalize Risk Score parameter.
Filter Out Entries with No New Evidence	Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.

< Recorded Future Hash Risk List



Disabled ☐ Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

Description

This feed ingests Recorded Future Default Hash risk list.

Authentication Configuration

API Key

☐ Enable SSL Verification

☒ Disable Proxies

If true, specifies that this feed should not honor any proxies setup in ThreatQuotient.

Ingestion Options

Risk Rule Triggered (Optional)

Indicators are added to the default risk list if they trigger any existing Recorded Future risk rule. Enable this option to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected all the indicators satisfying the rest of the criteria are ingested.

- ☐ Reported by Insikt Group
- ☐ Reported by DHS AIS
- ☐ Historically Reported in Threat List
- ☐ Linked to Cyber Attack
- ☐ Linked to Malware
- ☐ Linked to Attack Vector
- ☐ Linked to Vulnerability
- ☐ Malware SSL Certificate Fingerprint
- ☐ Positive Sandbox Detection on File From Underground Virus Testing Sites
- ☐ No Risk Observed
- ☐ Observed in Underground Virus Testing Sites

Recorded Future IP Risk List Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Risk Rule Triggered	Optional - Enable this parameter to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected, all the indicators satisfying the rest of the criteria are ingested. Options include: ◦ Threat Actor Used Infrastructure ◦ Historically Reported by Insikt Group ◦ Inside Possible Bogus BGP Route ◦ Historical Botnet Traffic ◦ Historical Brute Force ◦ Nameserver for C&C Server ◦ Cyber Exploit Signal: Critical ◦ Cyber Exploit Signal: Important ◦ Cyber Exploit Signal: Medium ◦ Recent Host of Many DDNS Names ◦ Historical DDoS ◦ Recent DNS Abuse ◦ Recent Honeypot Sighting ◦ Recently Linked to Intrusion Method ◦ Recently Linked to APT ◦ Recently Linked to Cyber Attack ◦ Recent Malicious Infrastructure Admin Server ◦ Recent Malware Delivery ◦ Recent Multicategory Blocklist ◦ Recent Open Proxies ◦ Recent Phishing Host ◦ Recent Positive Malware Verdict

PARAMETER	DESCRIPTION
- Historically Reported as a Defanged IP - Historically Reported by DHS AIS - Historical DNS Abuse - Resolution of Fast Flux DNS Name - Historically Reported in Threat List - Historical Honeypot Sighting - Honeypot Host - Recently Communicating Validated C&C Server - Historically Linked to Intrusion Method - Historically Linked to APT - Historically Linked to Cyber Attack - Historical Malicious Infrastructure Admin Server - Suspected Malicious Packet Source - Historical Malware Delivery - Historical Multicategory Blocklist - Observed in the Wild by Recorded Future Telemetry - Historical Open Proxies - Historical Phishing Host - Historical Positive Malware Verdict	- Recently Referenced by Insikt Group - Recently Reported C&C Server - Recently Communicating With Reported C&C Server - Recent Spam Source - Recent SSH/Dictionary Attacker - Recent Bad SSL Association - Recent Suspected C&C Server - Recent Threat Researcher - Recent Tor Node - Recent Unusual IP - Validated C&C Server - Recently Communicating With Validated C&C Server - Recently Defaced Site - Historically Referenced by Insikt Group - Historically Reported C&C Server - Trending in Recorded Future Analyst Community - Historical Spam Source - Historical SSH/Dictionary Attacker - Historical Bad SSL Association - Historical Suspected C&C Server - Suspected Phishing Host

PARAMETER	DESCRIPTION
	- Recorded Future Predictive Risk Model - Actively Communicating Validated C&C Server - Recently Reported by Insikt Group - Recent Botnet Traffic - Recent Brute Force - Recent DDoS - Recently Reported as a Defanged IP - Recently Reported by DHS AIS - Historical Threat Researcher - Tor Node - Unusual IP - Previously Validated C&C Server - Vulnerable Host - Observed High-Impact Vulnerability
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>

PARAMETER

DESCRIPTION



This parameter is only accessible if you have enabled the **Normalize Risk Score** parameter.

Filter Out Entries with No New Evidence

Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.

< Recorded Future IP Risk List



Disabled ☐ Enabled ☒

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

Description

This feed ingests Recorded Future Default IP risk list

Authentication Configuration

API Key

☐ Enable SSL Verification

☒ Disable Proxies

If true, specifies that this feed should not honor any proxies setup in ThreatQuotient

Ingestion Options

Risk Rule Triggered (Optional)

Indicators are added to the default risk list if they trigger any existing Recorded Future risk rule. Enable this option to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected all the indicators satisfying the rest of the criteria are ingested.

- ☐ Threat Actor Used Infrastructure
- ☐ Historically Reported by Insikt Group
- ☐ Inside Possible Bogus BGP Route
- ☐ Historical Botnet Traffic
- ☐ Historical Brute Force
- ☐ Nameserver for C&C Server
- ☐ Cyber Exploit Signal: Critical
- ☐ Cyber Exploit Signal: Important
- ☐ Cyber Exploit Signal: Medium
- ☐ Recent Host of Many DDNS Names
- ☐ Historical DDoS

Recorded Future URL Risk List Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Risk Rule Triggered	Optional - Enable this parameter to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected, all the indicators satisfying the rest of the criteria are ingested. Options include: ◦ Historically Reported by Insikt Group ◦ Historically Reported Botnet URL ◦ Historical C&C URL ◦ Historically Reported as a Defanged URL ◦ Historically Reported by DHS AIS ◦ Historically Reported Fraudulent Content ◦ Historically Reported in Threat List ◦ Historically Detected Malware Distribution ◦ Historically Suspected Malware Distribution ◦ Recently Reported as a Defanged URL ◦ Recently Reported by DHS AIS ◦ Recently Reported Fraudulent Content ◦ Recently Detected Malware Distribution ◦ Recently Suspected Malware Distribution ◦ Recently Detected Cryptocurrency Mining Techniques ◦ Recently Detected Phishing Techniques ◦ Recently Suspected Phishing Techniques

PARAMETER	DESCRIPTION
	◦ Historically Detected Cryptocurrency Mining Techniques ◦ No Risk Observed ◦ Observed in the Wild by Recorded Future Telemetry ◦ Historically Detected Phishing Techniques ◦ Historically Suspected Phishing Techniques ◦ Historically Detected Web Filter Avoidance Proxy URL ◦ Recently Reported by Insikt Group ◦ Recently Reported Botnet URL ◦ Recent C&C URL ◦ Recent Web Filter Avoidance Proxy URL ◦ Recently Referenced by Insikt Group ◦ Recent Reported C&C URL ◦ Recently Reported Spam or Unwanted Content ◦ Recent Suspected C&C URL ◦ Recently Active URL on Weaponized Domain ◦ Historically Referenced by Insikt Group ◦ Historical Reported C&C URL ◦ Historically Reported Spam or Unwanted Content ◦ Historical Suspected C&C URL
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, <code>Normalized Risk</code>. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium</pre>

PARAMETER	DESCRIPTION
	51,75,High 76,100,Critical  This parameter is only accessible if you have enabled the Normalize Risk Score parameter.
Filter Out Entries with No New Evidence	Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.

[< Recorded Future URL Risk List](#)



Disabled
 ☒
 Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

Description

This feed ingests Recorded Future Default URL risk list

Authentication Configuration

API Key

☐ Enable SSL Verification

☒ Disable Proxies

If true, specifies that this feed should not honor any proxies setup in ThreatQuotient

Ingestion Options

Risk Rule Triggered (Optional)

Indicators are added to the default risk list if they trigger any existing Recorded Future risk rule. Enable this option to ingest only indicators that triggered any of the selected risk rules. If no risk rule is selected all the indicators satisfying the rest of the criteria are ingested.

- ☐ Historically Reported by Insikt Group
- ☐ Historically Reported Botnet URL
- ☐ Historical C&C URL
- ☐ Historically Reported as a Defanged URL
- ☐ Historically Reported by DHS AIS
- ☐ Historically Reported Fraudulent Content
- ☐ Historically Reported in Threat List
- ☐ Historically Detected Malware Distribution
- ☐ Historically Suspected Malware Distribution
- ☐ Historically Detected Cryptocurrency Mining Techniques
- ☐ No Risk Observed

Recorded Future Analyst Note Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Entity	A string to search for notes by entity ID.
Title	A string to search for notes by title.
Topic	A string to search for notes by topic ID. Options include: • Actor Profile • Analyst On-Demand Report • Cyber Threat Analysis • Flash Report • Geopolitical Intelligence Summary • Geopolitical Flash Event • Geopolitical Threat Forecast • Geopolitical Validated Event • Hunting Package • Indicator • Insikt Research Lead • Informational • Malware/Tool Profile • Regular Vendor Vulnerability Disclosures • Sigma Rule • SNORT Rule • Source Profile • The Record by Recorded Future • Threat Lead • TTP Instance • Validated Intelligence Event • Weekly Threat Landscape • YARA Rule
Label	A string that helps searching for notes by label, by name.
Source	A string that helps sorting by the source of note. The options for this user field will be:

PARAMETER	DESCRIPTION
	◦ Insikt Group ◦ ThreatQuotient - Partner Notes
Tagged Text	Enable this parameter if the text should contain tags.
Fetch & Ingest Attachments	Enable this parameter to fetch any attachments associated with a given analyst note.
Extracted Signatures	Select which signature types to parse and ingest from relevant analyst note attachments. Options include: ◦ YARA (<i>default</i>) ◦ Snort (<i>default</i>) ◦ Sigma ◦ Nuclei  Sigma and Nuclei rules will be ingested with the Custom signature type and a Type attribute for the specific rule type.
Ingest CVEs As	Select which ThreatQ entity type to ingest CVE values as in ThreatQ. Options include Vulnerabilities (default) and Indicators .
Ingest Selected Primary Entities as Indicators	Select which entity types to ingest as indicators of compromise into ThreatQ. Options include: ◦ URLs (default) ◦ Internet Domain Names (default) ◦ IP Addresses (default) ◦ Hashes (default) ◦ Email Addresses (default) ◦ Usernames ◦ Filenames

PARAMETER	DESCRIPTION
	 This will only ingest the selected types from the "primary" entities (note_entities), and not the "supporting" entities (context_entities). This is so we can reduce the amount of false positives being ingested into the platform. Even if you do not select any of these, they will still be included in the description of the note.
Ingest Selected Supporting Entities as Indicators	Select which entity types to ingest as indicators of compromise into ThreatQ. Options include: ◦ URLs ◦ Internet Domain Names ◦ IP Addresses ◦ Hashes ◦ Email Addresses ◦ Usernames ◦ Filenames  This will only enable the ingestion of the selected types from the "supporting" entities (context_entities), and not the "primary" entities (note_entities). ThreatQuotient does not recommend enabling option due to the high likelihood of false positives. Even if you do not select any of these, they will still be included in the description of the note.
Ingested Hash Types	Select the type of hashes to be ingested into ThreatQ. Options include ◦ MD5 ◦ SHA-1 ◦ SHA-256

PARAMETER	DESCRIPTION
Ingest Topics As	Select the ThreatQ entity type to ingest topics as in the platform. Options include Tags and Attributes .
API Request Limit	The maximum number of records per request. This will be used in the pagination.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.

[<](#) Recorded Future Analyst Note



Disabled ☒ Enabled

 Run Integration

 Uninstall

Additional Information

 Integration Type: Feed

 Version:

Configuration

Activity Log

API Key

Entity (Optional)

 Filter by Report Entity ID

Title (Optional)

 Filter by Report Title

Topic (Optional)

 Notes by Report Topic ID

Label (Optional)

 Filter by Report Label Name

Source (Optional)

 Filter by Report Source

☐ Tagged Text (Optional)

Select whether the text should contain tags or not.

☒ Fetch & Ingest Attachments

Select whether to fetch any attachments associated with a given analyst note.

Extracted Signatures

Select which signature types to parse & ingest from relevant analyst note attachments.

☒ YARA

☒ Snort

☒ Sigma

☒ Nuclei

Recorded Future Alerts Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Triggered	A string to search for events from a specific date (YYYY-MM-DD or YYYY-MM or YYYY).
Review Status	A string to search for events by status (Unassigned, Assigned, No Action and Tuning). If no specific status is selected, all event statuses are returned by the provider.
Freetext Search	A string to search for events by any value.
Ingest CVE Data as	Select whether to ingest CVEs as: Vulnerabilities or Indicators (type: CVE).
Ingested Hash Types	Select the type of hashes to be ingested into ThreatQ. Options include ◦ MD5 ◦ SHA-1 ◦ SHA-256
Ingest Indicator Hits	Select which indicator hits to ingest into ThreatQ. All ingested indicators will receive a status of 'Review' since hits are not always indicators of compromise. They may be your organization's domains found on the dark web, newly registered organization domains, or other non-malicious indicators. Options include: ◦ URLs ◦ Domains ◦ IP Addresses

PARAMETER	DESCRIPTION
	◦ Filenames
Ingest Emails as Compromised Accounts for These Rules	Enter a line-separated list of rule names (or IDs) that will be used to determine if an email address should be ingested as a Compromised Account object or Identity object. Recorded Future creates alerts for entities that have triggered a rule. These entities may be of different types such as: IP addresses, URLs, email addresses, etc. This parameter allows you to determine if an email address is a compromised Account when Recorded Future creates an alert for it.
Ingest Images as Files Related to Alerts	Enable this option to download and ingest images into the ThreatQ platform as related Files.
Ingest and Relate "triggered_by" Entities to Alerts	Enable this option to ingest "triggered_by" entities related objects.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.

Recorded Future Alerts



Disabled Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

API Key

API Key _____

Triggered

Get events from a specific date (YYYY-MM-DD or YYYY-MM or YYYY) (optional)

Review Status

Review Status (Optional)

Freetext Search

Freetext search for events by any value (Optional)

— Ingest CVEs As

Indicators (Type: CVE)

Select which ThreatQ entity type to ingest CVE values as.

Ingested Hash Types

The hash types to be ingested into ThreatIQ.

- ☐ MD5
- ☐ SHA-1
- ☐ SHA-256

Ingest Indicator Hits

Select which indicator hits to ingest into ThreatQ. All ingested indicators will receive a status of 'Review' since hits are not always indicators of compromise. They may be your organization's domains found on the dark web, newly registered organization domains, or other non-malicious indicators.

- ☐ URLs
- ☐ Domains
- ☐ IP Addresses
- ☐ Filenames

Recorded Future Playbook Alerts Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Statuses	The Status of the Playbook Alert. Options include: ◦ New ◦ In Progress ◦ Dismissed ◦ Resolved
Playbook Category Filter	Select which playbook categories to ingest. Options include: ◦ Domain Abuse (default) ◦ Cyber Vulnerability (default) ◦ Code Repo Leakage (default) ◦ Third Party Risk (default) ◦ Identify Novel Exposures (<i>default</i>)
Priority	The Priority of the Playbook Alert. Options include: ◦ High Priority ◦ Moderate Priority ◦ Priority Informational
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string

PARAMETER	DESCRIPTION
	with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>  This parameter is only accessible if you have enabled the Normalize Risk Score parameter.
Ingest Target Attributes	Enable this parameter to ingest Targets as event attributes and related indicator attributes. This parameter is enabled by default.
Ingest CVEs as	Select whether to ingest CVEs as: Vulnerabilities or Indicators (type: CVE).
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.

Recorded Future Playbook Alerts



Disabled Enabled

Run Integration

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

API Key =

000

Filter By:

Creation time of the Playbook Alert

Statuses

The Status of the Playbook Alert

- ☒ New
- ☒ In Progress
- ☒ Dismissed
- ☒ Resolved

Playbook Category Filter

Select which playbook categories to ingest into ThreatQ.

- ☒ Domain Abuse
- ☒ Cyber Vulnerability
- ☒ Code Repo Leakage
- ☒ Third Party Risk
- ☒ Identity Novel Exposures

Priority

The Priority of the Playbook Alert

- ☒ High priority
- ☒ Moderate priority
- ☒ Priority informational

Risk Score Normalization Option

- ☐
- Normalize Risk Score

Enabling this will allow to ingest a normalized risk score value to a scoreable attribute.

Recorded Future Fusion Files Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
Selected Fusion Feeds	Select the Fusion Files to be retrieved. Options include: ◦ Command and Control IPs ◦ Known TOR IPs ◦ Active RAT C2 IPs ◦ Fast Flux IPs ◦ IP Risk List w/ Geolocation & Malware & ASN & Adversaries ◦ Dynamic DNS IPs ◦ Potentially Undetectable Malware ◦ Weaponized Domains ◦ Exploits in the Wild Hashes ◦ Hash Risk List w/ Malware & Adversaries ◦ Domain Risk List w/ Malware & Adversaries
Minimum Risk Score Threshold	The numeric value representing the minimum risk score required to ingest an IOC. The default setting is 50.  This parameter is only accessible if you have enabled the IP Risk List w/ Geolocation & Malware option is selected for the Selected Fusion Feeds parameter.
Normalize Risk Score	Enable this parameter ingest a normalized risk score value as a scorable attribute.

PARAMETER	DESCRIPTION
	 This parameter is only accessible if you have enabled the IP Risk List w/ Geolocation & Malware option is selected for the Selected Fusion Feeds parameter.
Risk Score Normalization Mapping	Mapping used to normalize the numeric risk score values to the scorable attribute, Normalized Risk. The Risk Score itself will always be ingested. This mapping should contain a line-separated CSV formatted string with the following columns: Minimum, Maximum, and Normalized Value. Default Values <pre>0,25,Low 26,50,Medium 51,75,High 76,100,Critical</pre>  This parameter is only accessible if you have enabled the IP Risk List w/ Geolocation & Malware option is selected for the Selected Fusion Feeds parameter.
Filter Out Entries with No New Evidence	Enabling this option will filter out entries that have no new evidence. A risk list is a rolling list of indicators. As a result, there are entries within the list that may be from days, months, or even years ago. Once the feed runs historically and ingests all the entries, subsequent runs do not need to re-ingest the same entries again if there is no new evidence. Disabling it will re-ingest all entries, with solely the old evidence being filtered out. This parameter is enabled by default.
Ingest ASN As	Select which ThreatQ entity type to ingest ASN values as for supported Fusion Files. Options include: ◦ Attribute (<i>default</i>)

PARAMETER	DESCRIPTION
	◦ Related Indicator  This parameter is only accessible if you have enabled the Active RAT C2 IPs or IP Risk List w/ GeoLocation & Malware & ASN & Adversaries options are selected for the Selected Fusion Feeds parameter.
Ingest Related Malware	Enabling this will ingest Malware related to indicators in the feeds.  It is important to note that over time, this may create a large number of relationships between indicators and malware.
Ingest Related Adversaries	Enabling this will ingest Adversaries related to indicators in the feeds.  It is important to note that over time, this may create a large number of relationships between indicators and adversaries.
Ingest Related CVEs	Optional - Enabling this will ingest CVEs related to indicators in the feeds.  This parameter only applies to the Exploits in the Wild feed and is disabled by default due to the large number of CVE relationships that may be created when enabled. Exercise caution when enabled this parameter.
Ingest CVEs As	Select whether to ingest CVEs as Vulnerabilities (default) or Indicators.

PARAMETER

DESCRIPTION



This parameter is only accessible if you have enabled the **Ingest Related CVEs** parameter selected.

Enable SSL Verification

Enable this for the feed to validate the host-provided SSL certificate.

Disable Proxies

Enable this option if the feed should not honor proxies set in the ThreatQ UI.

< Recorded Future Fusion Files



Disabled ☐ Enabled ☒

Uninstall

Additional Information

Integration Type: Feed

Version:

Configuration Activity Log

API Key

Selected Fusion Feeds

- ☐ Command and Control IPs
- ☐ Known TOR IPs
- ☐ Active RAT C2 IPs
- ☐ Fast Flux IPs
- ☒ IP Risk List w/ GeoLocation & Malware & ASN & Adversaries
- ☐ Dynamic DNS IPs
- ☐ Potentially Undetectable Malware
- ☐ Weaponized Domains
- ☐ Exploits in the Wild Hashes
- ☐ Hash Risk List w/ Malware & Adversaries
- ☐ Domain Risk List w/ Malware & Adversaries

Minimum Risk Score Threshold

50

Numeric value representing the minimum risk score required to ingest an IOC.

- ☐ Normalize Risk Score

Recorded Future Detection Rules Parameters

PARAMETER	DESCRIPTION
API Key	Your API Key to be used in HTTP headers for accessing feed data.
API Request Limit	Enter the maximum number of objects per request. This will be used in the pagination.
Enable SSL Verification	Enable this for the feed to validate the host-provided SSL certificate.
Disable Proxies	Enable this option if the feed should not honor proxies set in the ThreatQ UI.
Rule Types	Select which rule types to fetch and ingest from the Recorded Future API. Options include: ◦ YARA (default) ◦ Snort (default) ◦ Sigma
Ingest Selected Entities as Indicators	Select which entity types to ingest as indicators of compromise into ThreatQ. Options include: ◦ URLs ◦ Internet Domain Names ◦ IP Addresses ◦ Hashes ◦ Email Addresses ◦ Usernames ◦ Filenames
Ingested Hash Types	Select the hash types to ingest. Options include: ◦ MD5

PARAMETER	DESCRIPTION
	◦ SHA-1 ◦ SHA-256
Ingest CVEs as	Select whether to ingest CVEs as: Vulnerabilities or Indicators (type: CVE).

◀ Recorded Future Detection Rules



Disabled ☒ Enabled

Run Integration

Uninstall

Additional Information
Integration Type: Feed
Version:

Configuration

Activity Log

API Key

API Request Limit

Maximum number of objects per request

☒ Enable SSL Verification
☒ Disable Proxies
If true, specifies that this feed should not honor any proxies setup in ThreatQuotient

Rule Types
Select which rule types to fetch and ingest from the Recorded Future API.

☒ YARA
☒ Snort
☒ Sigma

Ingest Selected Entities As Indicators
Select which entity types to ingest as indicators of compromise into ThreatQ.

☒ URLs
☒ Internet Domain Names
☒ IP Addresses
☒ Hashes
☒ Email Addresses
☐ Usernames
☐ Filenames

- Review any additional settings, make any changes if needed, and click on **Save**.
- Click on the toggle switch, located above the *Additional Information* section, to enable it.

ThreatQ Mapping

Recorded Future Domain Risk List

The Recorded Future Domain Risk List feed ingests data from the Recorded Future Default Domain Risk List in form of a CSV list. The first token is the actual risk data (domain), and the last token (EvidenceDetails) contains supporting context. This token is a JSON-formatted string of an array of dictionaries.

GET <https://api.recordedfuture.com/v2/domain/risklist>

Sample Response:

```
'ns513726.ip-192-99-148.net', '92', '3/32',
{'EvidenceDetails':
  [
    {
      "CriticalityLabel": "Unusual",
      "Rule": "Historical Malware Analysis DNS Name",
      "EvidenceString": "6 sightings on 1 source:
VirusTotal...",
      "Timestamp": "2015-04-04T00:00:00.000Z",
      "Criticality": 1
    },
    {
      "CriticalityLabel": "Suspicious",
      "Rule": "Blacklisted DNS Name",
      "EvidenceString": "1 sighting on 1 source: DShield:
Suspicious Domain List.",
      "Timestamp": "2018-12-26T07:12:00.936Z",
      "Criticality": 2
    },
    {
      "CriticalityLabel": "Very Malicious",
      "Rule": "C&C DNS Name",
      "EvidenceString": "1 sighting on 1 source: Abuse.ch: Zeus
Domain Blocklist (Standard).",
      "Timestamp": "2018-12-26T07:12:00.936Z",
      "Criticality": 4
    }
  ]
}
```

```
} ' ]
```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	FQDN	N/A	ns513726.ip-192-99-148.net	N/A
1 (second token)	Indicator.Attribute	Risk Score	N/A	66	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field; Updatable
2 (third token)	Indicator.Attribute	Risk String	N/A	2/32	Updatable
3 (fourth token) [].CriticalityLabel	Indicator.Attribute	Criticality	3 (fourth token) [].Timestamp	Suspicious	Updatable. The highest criticality level is selected.
3 (fourth token) [].Rule	Indicator.Attribute	Associated Rule	3 (fourth token) [].Timestamp	Blacklisted DNS Name	N/A
3 (fourth token) [].EvidenceString	Indicator.Attribute	Evidence	3 (fourth token) [].Timestamp	1 sighting on 1 source: Abuse.ch: Zeus Domain Blocklist (Standard).	N/A

Recorded Future IP Risk List

The Recorded Future IP Risk List feed ingests Recorded Future Default IP risk list. IP addresses are ingested as indicators.

GET <https://api.recordedfuture.com/v2/ip/risklist>

Sample CSV Response:

```
'5.120.187.119", '65', '1/49',
'{"EvidenceDetails":
  [
    {
      "CriticalityLabel": "Malicious",
      "Rule": "Recent Positive Malware Verdict",
      "EvidenceString": "1 sighting on 1 source:
ReversingLabs....",
      "Timestamp": "2018-11-22T00:00:00.000Z",
      "Criticality": 3
    }
  ]
}'
```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	IP Address	N/A	5.120.187.119	N/A
1 (second token)	Indicator.Attribute	Risk Score	N/A	65	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field; Updatable
2 (third token)	Indicator.Attribute	Risk String	N/A	1/49	Updatable
3 (fourth token) [].CriticalityLabel	Indicator.Attribute	Criticality	3 (fourth token) [].Timestamp	Malicious	Updatable. The highest criticality level is selected.
3 (fourth token) [].Rule	Indicator.Attribute	Associated Rule	3 (fourth token) [].Timestamp	Recent Positive Malware Verdict	N/A
3 (fourth token) [].EvidenceString	Indicator.Attribute	Evidence	3 (fourth token) [].Timestamp	1 sighting on 1 source: ReversingLabs .	N/A

Recorded Future URL Risk List

The Recorded Future URL Risk List feed ingests Recorded Future Default URL risk list. URLs are ingested as indicators.

GET <https://api.recordedfuture.com/v2/url/risklist>

Sample CSV Response:

```
'http://handle.booktobi.com/css/index.html', '65', '1/7',
{'EvidenceDetails':
  [
    {
      "CriticalityLabel": "Malicious",
      "Rule": "Active Phishing URL",
      "EvidenceString": "1 sighting on 1 source: PhishTank:
Phishing Reports.",
      "Timestamp": "2018-12-26T16:15:44.750Z",
      "Criticality": 3
    }
  ]
}'
```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	URL	N/A	http://handle.booktobi.com/css/index.html	N/A
1 (second token)	Indicator.Attribute	Risk Score	N/A	65	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field; Updatable
2 (third token)	Indicator.Attribute	Risk String	N/A	1/7	Updatable
3 (fourth token) [].CriticalityLabel	Indicator.Attribute	Criticality	3 (fourth token) [].Timestamp	Malicious	Updatable - the highest criticality level is selected.
3 (fourth token) [].Rule	Indicator.Attribute	Associated Rule	3 (fourth token) [].Timestamp	Active Phishing URL	N/A
3 (fourth token)	Indicator.Attribute	Evidence	3 (fourth token) [].Timestamp	1 sighting on 1 source: PhishTank:	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
[].EvidenceString				Phishing Reports.	

Recorded Future Vulnerability Risk List

The Recorded Future Vulnerability Risk List feed ingests Recorded Future Default Vulnerability risk list. CVEs are ingested as indicators or as vulnerabilities depending on user configuration.

GET <https://api.recordedfuture.com/v2/vulnerability/risklist>

Sample CSV Response:

```
'CVE-2018-0802', '89', '11/18',
{'EvidenceDetails':
  [
    {
      "CriticalityLabel": "Low",
      "Rule": "Linked to Historical Cyber Exploit",
      "EvidenceString": "4281 sightings on 351 sources
including: ...",
      "Timestamp": "2018-11-14T22:31:30.000Z",
      "Criticality": 1
    },
    {
      "CriticalityLabel": "Low",
      "Rule": "Historically Linked to Penetration Testing
Tools",
      "EvidenceString": "1 sighting on 1 source:
@DTechCloud....",
      "Timestamp": "2018-05-07T20:31:29.000Z", "Criticality": 1
    }
  ]
}'
```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value/ Vulnerability.Value	CVE/N/A	N/A	CVE-2018-0802	N/A
1 (second token)	Indicator.Attribute/ Vulnerability.Attribute	Risk Score	N/A	89	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field; Updatable

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
2 (third token)	Indicator.Attribute/Vulnerability.Attribute	Risk String	N/A	11/18	Updatable
3 (fourth token) [.CriticalityLabel]	Indicator.Attribute/Vulnerability.Attribute	Criticality	3 (fourth token) [.Timestamp]	Low	Updatable. The highest criticality level is selected.
3 (fourth token) [.Rule]	Indicator.Attribute/Vulnerability.Attribute	Associated Rule	3 (fourth token) [.TimeStamp]	Linked to Historical Cyber Exploit	N/A
3 (fourth token) [.EvidenceString]	Indicator.Attribute/Vulnerability.Attribute	Evidence	3 (fourth token) [.Timestamp]	1 sighting on 1 source: @DTechCloud. ...	N/A

Recorded Future Hash Risk List

The Recorded Future Hash Risk List feed ingests Recorded Future Default Hash risk list. Hashes are ingested as indicators.

GET <https://api.recordedfuture.com/v2/hash/risklist>

Sample CSV Response:

```
'ed01ebfbc9eb5bbea545af4d01bf5f1071661840480439c6e5babe8e080e41aa',
'SHA-256', '89', '4/10',
{'EvidenceDetails':
  [
    {
      "CriticalityLabel": "Unusual",
      "Rule": "Threat Researcher",
      "EvidenceString": "21 sightings on 9 sources
including: ...",
      "Timestamp": "2018-01-28T11:24:35.942Z",
      "Criticality": 1.0
    },
    {
      "CriticalityLabel": "Suspicious",
      "Rule": "Linked to Vulnerability",
      "EvidenceString": "5 sightings on 2 sources: ...",
      "Timestamp": "2017-08-08T14:10:11.410Z",
      "Criticality": 2
    },
    {
      "CriticalityLabel": "Suspicious",
      "Rule": "Linked to Malware",
      "EvidenceString": "Previous sightings on 36 sources
including: ...",
      "Timestamp": "2017-05-12T15:39:30.000Z",
      "Criticality": 2
    }
  ]
}'
```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	1 (second token)	N/A	00d48afbba5ef9eadb572730b2d0cfaa	N/A
2 (third token)	Indicator.Attribute	Risk Score	N/A	89	Updatable
2 (third token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field; Updatable
3 (fourth token)	Indicator.Attribute	Risk String	N/A	4/10	Updatable
4 (fifth token) [].CriticalityLabel	Indicator.Attribute	Criticality	4 (fifth token) [].Timestamp	Suspicious	Updatable. The highest criticality level is selected.
4 (fifth token) [].Rule	Indicator.Attribute	Associated Rule	4 (fifth token) [].Timestamp	Linked to Malware	N/A
4 (fifth token) [].EvidenceString	Indicator.Attribute	Evidence	4 (fifth token) [].Timestamp	Previous sightings on 36 sources including: ...	N/A

Recorded Future Analyst Note

The Recorded Future Analyst Note feed ingests Reports, Indicators and Attack Patterns.

POST <https://api.recordedfuture.com/analyst-note/search>

Sample Response:

```
{
  "data": [
    {
      "source": {
        "id": "VKz42X",
        "name": "Insikt Group",
        "type": "Source"
      },
      "attributes": {
        "validated_on": "2020-02-06T06:59:32.784Z",
        "published": "2020-02-06T06:59:32.784Z",
        "text": "some text",
        "attachment": "APT_FIN7.yar",
        "topic": [
          {
            "id": "TXSFt0",
            "name": "Flash Report",
            "type": "Topic"
          }
        ],
        "title": "Mailto Ransomware Targets Enterprise
Networks",
        "note_entities": [
          {
            "id": "bLfMiL",
            "name": "Mailto Ransomware",
            "type": "Malware"
          }
        ],
        "context_entities": [
          {
            "id": "J6Uzb0",
            "name": "Bleeping Computer",
            "type": "Source"
          }
        ]
      }
    }
  ]
}
```

```

    }
  ],
  "validation_urls": [
    {
      "id": "url:url:https://
www.bleepingcomputer.com/news/security/mailto-netwalker-ransomware-
targets-enterprise-networks/",
      "name": "url:https://
www.bleepingcomputer.com/news/security/mailto-netwalker-ransomware-
targets-enterprise-networks/",
      "type": "URL "
    },
    {
      "id": "url:url:https://twitter.com/
VK_Intel/status/1225086186445733889?s=20",
      "name": "url:https://twitter.com/
VK_Intel/status/1225086186445733889?s=20",
      "type": "URL "
    }
  ]
},
{id": "cu1WGK"
}
],
"counts": {
  "returned": 10,
  "total": 19216
}
}

```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	EXAMPLES	NOTES
.data[].attributes.title	Report.Name	Report	"Mailto Ransomware Targets Enterprise Networks"	N/A
.data[].attributes.published	Report.Published_at	N/A	"2020-02-06T06:59:32.784Z"	This date will also be used for related indicators and attack patterns.
.data[].attributes	Report.Description	Description	"text"	Description formatted using context information like Metadata, Topics,

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	EXAMPLES	NOTES
es. text				Notes and Contextual Entities, and Reference URLs
.data[]. source. name	Report.Attribute/ Signature.Attribute/ Attachment.Attribute	Recorded Future Source	"Insikt Group"	N/A
.data[]. attributes. topic[]. name	Report.Attribute/ Signature.Attribute/ Attachment.Attribute	Topic Name	"Flash Report"	User-Configurable
.data[]. id	Report.Attribute/ Signature.Attribute/ Attachment.Attribute	Recorded Future URL	"https:// app.recordedfuture. com/portal/ research/analyst /doc:cu1WGK"	Link formatted using .id
.data[]. attributes. topic[]. name	Report.Tag/ Signature.tag/ Attachment.tag	N/A	"Informational"	User-Configurable
.data[]. attributes. context_ entities	N/A	N/A	N/A	*See Entities Mapping
.data[]. attributes. note_ent ities	N/A	N/A	N/A	*See Entities Mapping
.data[]. attributes. attachme nt	Attachment.Value	N/A	APT_FIN7.yar	User-Configurable. The .data[].attributes.attachment is used to download the file.
.data[]. attributes. attachme nt	Signature.Value	Yara, Snort, Custom(Sigma,Nuc lei)	N/A	User-Configurable. The content of the .data[].attributes.attachment downloaded file. Signature are also related to ingested Attachments, Malware and Adversaries.
.data[]. attributes. attachme nt	Signature.Attribute	<Various Names>	N/A	Parsed from the content of the .data[].attributes.attachment downloaded file.
.data[]. attributes. attachme nt	Signature Related Indicators	<Various Types>	N/A	Parsed from the content of the .data[].attributes.attachment downloaded file.

Entities Mapping

This mapping will be used to map both values from `context_entities` and `note_entities`. The data sample and mapping are below:

Sample Response:

```
{
  "context_entities": [
    {
      "id": "J6Uzb0",
      "name": "Bleeping Computer",
      "type": "Source",
      "description": "some description"
    }
  ]
}
```

```
indicator_type_map:
  InternetDomainName: FQDN
  URL: URL
  IpAddress: IP Address
  EmailAddress: Email Address
  FileName: Filename
  Username: Username
  Hash: MD5, SHA-1, SHA-256
  CyberVulnerability: CVE
```

```
premapped_entities:
  - Malware
  - MitreAttackIdentifier
  - CyberVulnerability
  - Hashtag
  - Image
```

The integration will filter based by type. If the value of the `type` key is contained in the `indicator_type_map` below or is equal to `Hash`, an indicator will be ingested (the `published_at` date will be the same as for the report object). If the `type` key is equal to `Malware`, an object of type `Malware` type will be ingested. If the `type` key is equal to `MitreAttackIdentifier`, an object of `Attack Pattern` type will be ingested. Else, attributes will be created for the main `report` object.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	EXAMPLES	NOTES
.name	Report.Attribute/Indicator.Attribute	.type	N/A	*See Event Attributes Mapping below. If type is Product and there are related vulnerabilities, change the Product attribute key to Affected Product
.text	Report.Attribute	.description	N/A	N/A
.name	Indicator.Value	.type	98.123.54.12	IOC is enabled Ingest Selected Primary Entities as Indicators or Ingest Selected Supporting Entities as Indicators
.type	Indicator.Type	.name	Ip Address	The value for this will be indicator_type_map[.type] if it exists there. If the value is Hash, the value length will be analysed and based on it it will be either MD5, SHA-1, or SHA-256.
.name	Adversary.Value	N/A	N/A	If .type is Organization
.name	Adversary.Attribute	Category	"Bleeping Computer"	If .type is CyberThreatActorCategory
.name	Identity.Value	N/A	john.doe@acme.com	We ingest the Email Address as a Identity from "supporting" entities
.name	Attack Pattern.Value	N/A	T1023 - MITRE Technique Name	If type is equal to MitreAttackIdentifier
.name	Malware.Value	N/A	Mailto Ransomware	If .type is equal to Malware
.name	Malware.Attribute	Category	N/A	If .type id equal to MalwareCategory
.name	Vulnerability.Value	N/A	N/A	If the .type is equal to CyberVulnerability
.name	Vulnerability.Attribute/Indicator.Attribute	Affected Product	Citrix	Object type is based on Ingest CVEs As selection



Context (i.e. Malware, Adversaries, Attributes, and Attack Patterns) from the "primary" entities list will now be applied to the indicators of compromise from the "primary" entities list.

Recorded Future Alerts

The Recorded Future Alerts feed Recorded Future alerts as ThreatQ Events and all the related Indicators, Malware, Adversaries, Attack Patterns and Vulnerabilities, Image files and Entity objects.

GET <https://api.recordedfuture.com/alert/v3>

Sample Response:

```
{
  "data": [
    {
      "review": {
        "note": null,
        "status_in_portal": "New",
        "assignee": null,
        "status": "no-action"
      },
      "owner_organisation_details": {
        "organisations": [
          {
            "organisation_id": "uhash:ER135KQ6oL",
            "organisation_name": "ThreatQ - Partner"
          }
        ],
        "enterprise_id": "uhash:DimzHe41vx",
        "enterprise_name": "ThreatQ - Partner"
      },
      "url": {
        "api": "https://api.recordedfuture.com/v3/alerts/rj540x",
        "portal": "https://app.recordedfuture.com/live/sc/
notification/?id=rj540x"
      },
      "rule": {
        "name": "Cyber Espionage, Related Vulnerabilities",
        "id": "nt4XZZ",
        "url": {
          "portal": "https://app.recordedfuture.com/live/sc/
ViewIdkobra_view_report_item_alert_editor?
view_opts=%7B%22reportId%22%3A%22nt4XZZ%22%2C%22bTitle%22%3Atrue%2C%2
2title%22%3A%22Cyber+Espionage%2C+Related+Vulnerabilities%22%7D"
        }
      }
    }
  ]
}
```

```

},
"id": "rj540x",
"triggered_by": [
  {
    "entity_paths": [
      [
        {
          "attribute": {
            "id": "CredentialLeak.targets"
          },
          "entity": {
            "id": "email:s.grishin@delta.nl",
            "name": "s.grishin@delta.nl",
            "type": "EmailAddress"
          }
        }
      ]
    ]
  }
],
"hits": [
  {
    "entities": [
      {
        "id": "img:e2cd9495-937b-40a4-b5d7-f0fe89184040",
        "name": "e2cd9495-937b-40a4-b5d7-f0fe89184040",
        "type": "Image"
      },
      {
        "id": "B_HE4",
        "name": "Google",
        "type": "Company"
      },
      {
        "id": "idn:reuters.com",
        "name": "reuters.com",
        "type": "InternetDomainName"
      },
      {
        "id": "Xw2PY",
        "name": "Frankfurt",
        "type": "Airport"
      }
    ]
  }
]

```

```

    },
    {
      "id": "rVnb7k",
      "name": "Rhysida",
      "type": "Malware"
    },
    {
      "id": "J0Nl-p",
      "name": "Ransomware",
      "type": "MalwareCategory"
    },
    {
      "id": "K_4o-y",
      "name": "Anonymous Sudan",
      "type": "Organization"
    },
    {
      "id": "I_7J4G",
      "name": "Hacktivist",
      "type": "CyberThreatActorCategory"
    },
    {
      "id": "mitre:T1048",
      "name": "T1048",
      "type": "MitreAttackIdentifier"
    },
    {
      "id": "email:mary.silverstein@delta.com",
      "name": "mary.silverstein@delta.com",
      "type": "EmailAddress"
    },
    {
      "id": "jc5TL-",
      "name": "ProxyShell",
      "type": "CyberVulnerability",
      "description": "ProxyShell and Log4J Vulnerabilities
Were the Most Exploited Flaws in 2021."
    }
  ],
  "document": {
    "source": {
      "id": "source:hPTFPY",

```

```

        "name": "RedAlert | Blog",
        "type": "Source"
    },
    "title": "2022 Activities Summary of SectorA groups
(ENG)",
    "url": "https://redalert.nshc.net/2023/06/08/2022-
activities-summary-of-sectora-groups-eng/",
    "authors": []
},
    "fragment": "In this operation, the group targeted
engineering companies in the e id=0qjp>energyth an initial
infiltration method.",
    "id": "HE-xwAAZh-v",
    "language": "eng",
    "primary_entity": {
        "id": "kvXvR5",
        "name": "CVE-2021-44228",
        "type": "CyberVulnerability",
        "description": "Apache Log4j2 2.0-beta9 through 2.15.0
(excluding security releases 2.12.2, 2.12.3, and 2.3.1) JNDI features
used in configuration, log messages, and parameters do not protect
against attacker controlled LDAP and other JNDI related endpoints. An
attacker who can control log messages or log message parameters can
execute arbitrary code loaded from LDAP servers when message lookup
substitution is enabled. From log4j 2.15.0, this behavior has been
disabled by default. From version 2.16.0 (along with 2.12.2, 2.12.3,
and 2.3.1), this functionality has been completely removed. Note that
this vulnerability is specific to log4j-core and does not affect
log4net, log4cxx, or other Apache Logging Services projects."
    },
    "analyst_note": null
}
],
    "ai_insights": {
        "comment": "The Recorded Future AI requires more references
in order to produce a summary.",
        "text": null
    },
    "log": {
        "note_author": null,
        "note_date": null,
        "status_date": null,

```

```

      "triggered": "2023-06-08T04:53:13.444Z",
      "status_change_by": null
    },
    "title": "Cyber Espionage, Related Vulnerabilities - Rise:
CVE-2021-44228",
    "type": "ENTITY"
  }
],
"counts": {
  "returned": 10,
  "total": 2653
}
}

```

ThreatQuotient provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.data[].title	Event.Title	N/A	.data[].log.note_date / .data[].log.triggered	Cyber Espionage, Related Vulnerabilities - Rise: CVE-2021-44228	If .data[].log.note_date is not present .data[].log.triggered is used as Published Date
.data[].log.triggered	Event.Happened_at	N/A	N/A	2023-06-08T04:53:13.444Z	N/A
.data[].* (See Notes)	Event.Description	N/A	N/A	The Recorded Future AI requires more references in order to produce a summary...	Description is constructed from different Alert details, for example: Alert Metadata, AI Insights, and Hits information
.data[].id	Event.Attribute	Alert ID	.data[].log.note_date / .data[].log.triggered	N/A	N/A
.data[].review.assignee	Event.Attribute	Assignee	.data[].log.note_date / .data[].log.triggered	N/A	Updatable
.data[].log.note_author	Event.Attribute	Note Author	.data[].log.note_date / .data[].log.triggered	N/A	N/A
.data[].review.status_in_portal	Event.Attribute	Alert Status	.data[].log.note_date / .data[].log.triggered	no-action	Updatable
.data[].rule.name	Event.Attribute	Triggered Rule Name	.data[].log.note_date / .data[].log.triggered	Cyber Espionage, Related Vulnerabilities	N/A
.data[].type	Event.Attribute	Alert Type	.data[].log.note_date / .data[].log.triggered	ENTITY	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.data[].owner_organization_details.entity_name	Event.Attribute	Organisation Enterprise name	.data[].log.note_date / .data[].log.triggered	ThreatQ - Partner	N/A
.data[].hits[].document.url	Event.Attribute	URL	N/A	https://www.virustotal.com/84387248326473645	Ingested as attribute if 'www.virustotal.com' in .url
.data[].hits[].entities[].name	Event.Tags	N/A	N/A	ddosattacks	If data.hits[].entities[].type is Hashtag. Character # is removed.
.data[].hits[].entities[].name	Indicator.Value	data.hits[].entities[].type	N/A	N/A	See Related Indicator Type Mapping table below.
.data[].rule.name	Indicator.Attribute	Entity Discovered by Rule	N/A	Cyber Espionage, Related Vulnerabilities	N/A
.data[].hits[].entities[].name	Event.Attribute	data.hits[].entities[].type	N/A	N/A	See Event Attributes Mapping table below.
.data[].hits[].entities[].name	Related.Malware.Value	N/A	N/A	Rhysida	If data.hits[].entities[].type is Malware
.data[].hits[].entities[].name	Event.Attribute	Malware Category	N/A	Ransomware	If data.hits[].entities[].type is MalwareCategory
.data[].hits[].entities[].name	Event.Attribute	Organization	N/A	Anonymous Sudan	If data.hits[].entities[].type is Organization and it is not an Adversary
.data[].hits[].entities[].name	Related.Adversary.Value	N/A	N/A	Anonymous Sudan	If data.hits[].entities[].type is Organization
.data[].hits[].entities[].name	Event.Attribute	Cyber Threat Actor Category	N/A	Hacktivist	If data.hits[].entities[].type is CyberThreatActorCategory
.data[].hits[].entities[].name	Related.AttackPattern.Value	N/A	N/A	T1048	If data.hits[].entities[].type is MitreAttackIdentifier
.data[].hits[].entities[].name	Related.Vulnerability.Value	N/A	N/A	ProxyShell	If data.hits[].entities[].type is CyberVulnerability or user config Save CVE Data as contains Vulnerabilities

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.data[].hits[].entities[].description	Related.Vulnerability.Description	N/A	N/A	ProxyShell and Log4J Vulnerabilities Were the Most Exploited Flaws in 2021.	If data.hits[].entities[].type is CyberVulnerability or user config Save CVE Data as contains Vulnerabilities
.data[].hits[].entities[].name	Related.Identity.Value	N/A	N/A	john.doe@acme.com	If data.hits[].entities[].type is EmailAddress
.data[].hits[].entities[].name	Related.Account.Value	N/A	N/A	john.doe@acme.com	If data.hits[].entities[].type is EmailAddress && Compromised Account Rule is configured & matched
.data[].hits[].entities[].name	Related.File	N/A	N/A	"Recorded_future_e2cd9495-937b-40a4-b5d7-f0fe89184040"	The ID is used to download the image in a supplemental call, if data.hits[].entities[].type is Image. User-configurable.
.data[].triggered_by[].entity_paths[].entity.name	Related.Entity.Title	N/A	N/A	s.grishin@delta.nl	User-configurable.
.data[].triggered_by[].entity_paths[].entity.type	Entity.Attribute	RF Type	N/A	EmailAddress	N/A
.data[].triggered_by[].entity_paths[].entity.id	Entity.Attribute	Entity ID	N/A	email:s.grishin@delta.nl	N/A
.data[].triggered_by[].entity_paths[].attribute.id	Entity.Attribute	RF_ID	N/A	CredentialLeak.targets	N/A



In the previous table, there is a Related Indicator that is set dynamically. This is because the ThreatQ Object Type is extracted from the same path `.data.hits[].entities[].type` if the `.data.hits[].entities[].type` is one from the Related Indicator Type Mapping table listed below.

Related Indicator Type Mapping

RECORDED FUTURE INDICATOR TYPE	THREATQ INDICATOR TYPE	NOTES
Hash	MD5	If the length of the hash value is 32 characters.
Hash	SHA-1	If the length of the hash value is 40 characters.
Hash	SHA-256	If the length of the hash value is 64 characters.
CyberVulnerability	CVE	If '.data.hits[].entities[].name' contains 'CVE' and user config Save CVE Data as contains Indicators.
URL	URL	N/A
Domain	FQDN	N/A
IPAddress	IP Address	N/A
FileName	Filename	N/A
InternetDomainName	FQDN	N/A

Event Attributes Mapping

In the previous table, **Related Indicator Type Mapping**, there is a **Related Indicator Attribute** that is set dynamically. We do this because the **Attribute Key** is extracted from the same path `.data.hits[].entities[].type` if the `.data.hits[].entities[].type` is one from the table listed below.

RECORDED FUTURE ATTRIBUTE TYPE	THREATQ ATTRIBUTE KEY
AttackVector	Attack Vector
Product	Affected Product
Company	Company
City	City
Country	Country
Facility	Facility
FileNameExtension	File Extension
FileType	File Type
GeoEntity	Geo Entity
Industry	Industry
IndustryTerm	Industry Term
Logotype	Logotype
Operation	Operation
OrgEntity	Organization Entity

RECORDED FUTURE ATTRIBUTE TYPE	THREATQ ATTRIBUTE KEY
PhoneNumber	Phone Number
ProvinceOrState	State
Region	Region
Technology	Technology
Topic	Topic

Recorded Future Playbook Alerts

The Recorded Future Playbook Alerts feed retrieves a list of alerts filtered by the values provided in the configuration section. For each of the alerts, the `playbook_alert_id` is used to call the Recorded Future - Get Playbook Alerts by Category supplemental feed, to fetch the full alert context.

POST <https://api.recordedfuture.com/playbook-alert/search>

Sample Response:

```
{
  "status": {
    "status_code": "Ok",
    "status_message": "Playbook alert search successful"
  },
  "data": [
    {
      "playbook_alert_id": "task:2803c5f5-aa32-41ce-98c1-41a7771cd9ad",
      "created": "2022-11-08T09:44:02.447Z",
      "updated": "2022-11-08T09:44:06.584Z",
      "status": "New",
      "category": "domain_abuse",
      "priority": "Informational",
      "title": "juhaokan.ga",
      "owner_id": "uhash:ER135KQ6oL",
      "owner_name": "ThreatQ - Partner",
      "organisation_id": "uhash:DimzHe41vx",
      "organisation_name": "ThreatQ - Partner"
    }
  ]
}
```

ThreatQuotient provides the following default mapping for this feed:



The mapping for this feed is based on the JSON response from the **Recorded Future - Get Playbook Alerts by Category supplemental feed**. Each mapping is based on an item within the data list within the JSON response.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.panel_status.case_rule_label, .panel_status.entity_name, .panel_status.priority, .panel_status.entity_criticality	Event.Title	Recorded Future Alert	.panel_status.created	Domain Abuse Alert: juhaokan.ga Priority: Informational Criticality: Medium	ThreatQ uses the four values to create an unique title
.panel_status.title	Event.Title	Recorded Future Alert	.panel_status.created	juhaokan.ga	N/A
.panel_evidence_summary.* , .panel_evidence_whois.*	Event.Description	N/A	N/A	N/A	Description HTML is built based on available fields
.panel_status.status	Event.Attribute	Status	.panel_status.created	New	Updatable
.panel_status.case_rule_label	Event.Attribute	Category	.panel_status.created	Domain Abuse	Updatable
.panel_status.priority	Event.Attribute	Priority	.panel_status.created	Informational	Updatable
.panel_status.owner_name	Event.Attribute	Owner	.panel_status.created	Acme Corp	Updatable
.panel_status.organisation_name	Event.Attribute	Organization	.panel_status.created	Acme Corp	N/A
.panel_status.assignee_name	Event.Attribute	Assignee	.panel_status.created	John Doe	N/A
.panel_status.lifecycle_stage	Event.Attribute	Lifecycle Stage	.panel_status.created	Disclosure	Only available for Cyber Vulnerability Alerts
.panel_status.entity_name	Related.Indicator	FQDN	.panel_status.created	jlonssdale.social	N/A
.panel_status.entity_name	Related.Vulnerability, Related.Indicator	CVE	.panel_status.created	CVE-2024-10234	N/A
.panel_status.risk_score	Event.Attribute, Related.Indicator.Attribute	Risk Score	.panel_status.created	5	Updatable
.panel_status.risk_score	Event.Attribute, Related.Indicator.Attribute	Normalized Risk	.panel_status.created	High	Mapped using Risk Score Normalization Mapping user field; Updatable
.panel_status.entity_criticality	Event.Attribute, Related.Indicator	Criticality	.panel_status.created	Low	Updatable

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
	cator.Attribute				
.panel_status.context_list[].context	Event.Attribute, Related.Indicator.Attribute	Context Data	.panel_status.created	Phishing Host	N/A
.panel_status.targets	Event.Attribute, Related.Indicator.Attribute	Target	.panel_status.created	idn:lonsdale.fr	User-configurable
.panel_evidence_dns.ip_list[].entity	Related.Indicator	IP Address	.panel_status.created	217.160.0.153	N/A
.panel_evidence_dns.ip_list[].record_type	Related.Indicator.Attribute	Record Type	.panel_status.created	N/A	Updatable
.panel_evidence_dns.ip_list[].risk_score	Related.Indicator.Attribute	Risk Score	.panel_status.created	27	Updatable
.panel_evidence_dns.ip_list[].risk_score	Related.Indicator.Attribute	Normalized Risk	.panel_status.created	Medium	Mapped using Risk Score Normalization Mapping user field; Updatable
.panel_evidence_dns.ip_list[].criticality	Related.Indicator.Attribute	Criticality	.panel_status.created	Medium	Updatable
.panel_evidence_dns.ip_list[].context_list[].context	Related.Indicator.Attribute	Context Data	.panel_status.created	Phishing Host	N/A
.panel_evidence_dns.mx_list[].entity	Related.Indicator	FQDN	.panel_status.created	mx00.ionos.co.uk	N/A
.panel_evidence_dns.mx_list[].record_type	Related.Indicator.Attribute	Record Type	.panel_status.created	N/A	Updatable
.panel_evidence_dns.mx_list[].risk_score	Related.Indicator.Attribute	Risk Score	.panel_status.created	0	Updatable
.panel_evidence_dns.mx_list[].risk_score	Related.Indicator.Attribute	Normalized Risk	.panel_status.created	Low	Mapped using Risk Score Normalization Mapping user field; Updatable
.panel_evidence_dns.mx_list[].criticality	Related.Indicator.Attribute	Criticality	.panel_status.created	0	Updatable
.panel_evidence_dns.mx_list[].context_list[].context	Related.Indicator.Attribute	Context Data	.panel_status.created	Active Mail Server	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.panel_evidence_dns.ns_list[].entity	Related.Indicator	FQDN	.panel_status.created	ns1025.ui-dns.org	N/A
.panel_evidence_dns.ns_list[].record_type	Related.Indicator.Attribute	Record Type	.panel_status.created	N/A	Updatable
.panel_evidence_dns.ns_list[].risk_score	Related.Indicator.Attribute	Risk Score	.panel_status.created	5	Updatable
.panel_evidence_dns.ns_list[].risk_score	Related.Indicator.Attribute	Normalized Risk	.panel_status.created	Low	Mapped using Risk Score Normalization Mapping user field; Updatable
.panel_evidence_dns.ns_list[].criticality	Related.Indicator.Attribute	Criticality	.panel_status.created	Low	Updatable
.panel_evidence_dns.ns_list[].context_list[].context	Related.Indicator.Attribute	Context Data	.panel_status.created	Active Mail Server	N/A
.panel_evidence_summary.affected_products[].name	Related.Vulnerability.Attribute	Affected Product	.panel_status.created	MySQL	Also applied to main event
.panel_evidence_summary.assessments[].evidence.data[].malwareIpAddress	Related.Indicator	IP Address	.panel_status.created	N/A	N/A
.panel_evidence_summary.assessments[].evidence.data[].malwareFamily	Related.Malware	N/A	.panel_status.created	Lazarus	N/A
.panel_evidence_summary.assessments[].evidence.data[].clientIpAddress	Related.Asset	N/A	.panel_status.created	N/A	N/A

Recorded Future - Get Playbook Alerts by Category (Supplemental)

The Recorded Future - Get Playbook Alerts by Category supplemental feed related data for each of the ingested events retrieved from the Alert endpoint. The key `.data[].playbook_alert_id` is used to call the supplemental feed.

POST `https://api.recordedfuture.com/playbook-alert/{{ category }}`



The API will return a slightly different response based on the category of the alert. See the Recorded Future Playbook Alerts feed for the mapping of the data.

Domain Abuse

Sample Response:

```
{
  "status": {
    "status_code": "Ok",
    "status_message": "Domain Abuse lookup successful"
  },
  "data": {
    "panel_status": {
      "entity_name": "lonsdale.social",
      "entity_criticality": "Low",
      "risk_score": 5,
      "context_list": [
        {
          "context": "Phishing Host"
        },
        {
          "context": "Active Mail Server"
        }
      ],
      "targets": [
        "idn:lonsdale.fr",
        "idn:lonsdale.us",
        "idn:lonsdale.porn",
        "idn:lonsdale.club"
      ],
      "status": "New",
      "priority": "High",
    }
  }
}
```

```

    "created": "2022-11-09T08:20:15.778Z",
    "case_rule_id": "report:nvAj-X",
    "case_rule_label": "Domain Abuse",
    "owner_id": "uhash:ER135KQ6oL",
    "owner_name": "ThreatQ - Partner",
    "organisation_id": "uhash:DimzHe41vx",
    "organisation_name": "ThreatQ - Partner"
  },
  "panel_action": [],
  "panel_evidence_summary": {
    "explanation": "Alert was created as a result of a
triggered typosquat detection",
    "resolved_record_list": [
      {
        "entity": "idn:ns1025.ui-dns.org",
        "risk_score": 5,
        "criticality": "Low",
        "record_type": "NS",
        "context_list": []
      },
      {
        "entity": "ip:217.160.0.153",
        "risk_score": 27,
        "criticality": "Medium",
        "record_type": "A",
        "context_list": [
          {
            "context": "Phishing Host"
          }
        ]
      },
      {
        "entity": "idn:mx00.ionos.co.uk",
        "risk_score": 0,
        "criticality": "0",
        "record_type": "MX",
        "context_list": [
          {
            "context": "Active Mail Server"
          }
        ]
      }
    ]
  },

```

```

        {
          "entity": "idn:mx01.ionos.co.uk",
          "risk_score": 0,
          "criticality": "0",
          "record_type": "MX",
          "context_list": [
            {
              "context": "Active Mail Server"
            }
          ]
        }
      ],
      "screenshots": [
        {
          "description": "An image associated with the
Playbook Alert",
          "image_id": "img:349f92e2-fa93-4282-be15-
e7a330130686",
          "created": "2022-11-09T08:20:51.685Z"
        }
      ]
    },
    "panel_evidence_dns": {
      "ip_list": [
        {
          "entity": "ip:217.160.0.153",
          "risk_score": 27,
          "criticality": "Medium",
          "record_type": "A",
          "context_list": [
            {
              "context": "Phishing Host"
            }
          ]
        }
      ]
    },
    "mx_list": [
      {
        "entity": "idn:mx00.ionos.co.uk",
        "risk_score": 0,
        "criticality": "0",
        "record_type": "MX",

```

```

        "context_list": [
            {
                "context": "Active Mail Server"
            }
        ]
    },
],
"ns_list": [
    {
        "entity": "idn:ns1115.ui-dns.de",
        "risk_score": 0,
        "criticality": "0",
        "record_type": "NS",
        "context_list": [
            {
                "context": "Active Mail Server"
            }
        ]
    },
    {
        "entity": "idn:ns1090.ui-dns.biz",
        "risk_score": 5,
        "criticality": "Low",
        "record_type": "NS",
        "context_list": []
    }
],
},
"panel_evidence_whois": {
    "body": [
        {
            "provider": "whois",
            "entity": "idn:lonsdale.social",
            "attribute": "attr:whois",
            "value": {
                "privateRegistration": false,
                "status": "clientTransferProhibited"
            }
        }
    ],
    "nameServers": [
        "idn:ns1066.ui-dns.com",
        "idn:ns1025.ui-dns.org",
        "idn:ns1115.ui-dns.de",

```

```

        "idn:ns1090.ui-dns.biz"
      ],
      "registrarName": "IONOS SE",
      "createdDate": "2022-11-08T19:44:16.000Z"
    },
    "added": "2022-11-09T08:21:13.682Z"
  },
  {
    "provider": "whois",
    "entity": "idn:btbo2.top",
    "attribute": "attr:whoisContacts",
    "value": {
      "organization": "REDACTED FOR PRIVACY",
      "city": "REDACTED FOR PRIVACY",
      "name": "REDACTED FOR PRIVACY",
      "state": "REDACTED FOR PRIVACY",
      "street1": "REDACTED FOR PRIVACY",
      "country": "REDACTED FOR PRIVACY",
      "postalCode": "REDACTED FOR PRIVACY",
      "telephone": "REDACTED FOR PRIVACY",
      "type": "technicalContact"
    },
    "added": "2022-11-08T10:28:20.712Z"
  }
]
},
"panel_log": [
  {
    "id": "uuid:26b4be48-e1e0-4773-97d7-b8c8260fe53b",
    "created": "2022-11-09T08:27:31.377Z",
    "modified": "2022-11-09T08:27:31.377Z",
    "action_priority": "Informational"
  }
]
}
}

```

Third Party Risk

Sample Response:

```
{
  "status": {
    "status_code": "Ok",
    "status_message": "Playbook alert bulk lookup successful."
  },
  "data": [
    {
      "playbook_alert_id":
"task:220833e1-6a00-489c-8e6f-08cb11561aea",
      "panel_status": {
        "status": "New",
        "priority": "Moderate",
        "created": "2024-05-09T18:03:42.784Z",
        "updated": "2024-05-13T05:11:28.845Z",
        "case_rule_id": "report:r2TUUz",
        "case_rule_label": "Third Party Risk",
        "owner_id": "uhash:1RmVv0sQ33",
        "owner_name": "Acme Corp",
        "organisation_id": "uhash:4WfuvVnaap",
        "organisation_name": "Acme Corp",
        "owner_organisation_details": {
          "organisations": [
            {
              "organisation_id": "uhash:4WfuvVnaap",
              "organisation_name": "Acme Corp"
            }
          ],
          "enterprise_id": "uhash:4WfuvVnaap",
          "enterprise_name": "Acme Corp"
        },
        "entity_id": "CEBTA",
        "entity_name": "Tele Communications",
        "entity_criticality": "Medium",
        "risk_score": 64,
        "targets": [
          {
            "name": "Infections Recently Reported in Company
Infrastructure"
          },
          {
            "name": "Recent Possible Malware in Company
Infrastructure"
          }
        ]
      }
    }
  ]
}
```

```

    ],
    "actions_taken": []
  },
  "panel_evidence_summary": {
    "assessments": [
      {
        "risk_rule": "Infections Recently Reported in Company
Infrastructure",
        "level": 2,
        "added": "2024-05-13T05:11:09.882Z",
        "evidence": {
          "type": "ip_rule",
          "summary": "4 sightings: Suspected Malicious Packet
Source seen for 1 IP Address on company infrastructure:
121.241.162.25. Recent Botnet Traffic seen for 3 IP Addresses on
company infrastructure: 203.199.243.0, 14.143.123.78,
14.143.187.214",
          "data": [
            {
              "name": "Suspected Malicious Packet Source",
              "criticality": 2,
              "number_of_ip_addresses": 1
            },
            {
              "name": "Recent Botnet Traffic",
              "criticality": 2,
              "number_of_ip_addresses": 3
            }
          ]
        }
      }
    ],
    {
      "risk_rule": "Recent Possible Malware in Company
Infrastructure",
      "level": 2,
      "added": "2024-05-13T05:11:09.882Z",
      "evidence": {
        "type": "ip_rule",
        "summary": "1 sighting: Recent Positive Malware Verdict
seen for 1 IP Address on company infrastructure: 14.142.45.148",
        "data": [
          {

```

```

        "name": "Recent Positive Malware Verdict",
        "criticality": 2,
        "number_of_ip_addresses": 1
      }
    ]
  }
}

```

Cyber Vulnerability

Sample Response:

```

{
  "status": {
    "status_code": "Ok",
    "status_message": "Playbook alert bulk lookup successful."
  },
  "data": [
    {
      "playbook_alert_id":
"task:174cd0d2-2fad-482b-956d-97e3c3e06ab3",
      "panel_status": {
        "status": "New",
        "priority": "Informational",
        "assignee_name": "John Doe",
        "assignee_id": "uhash:12QsDAJfc1",
        "created": "2024-04-25T14:10:30.241Z",
        "updated": "2024-04-25T14:10:30.241Z",
        "case_rule_id": "report:k0g1wZ",
        "case_rule_label": "Cyber Vulnerability",
        "owner_id": "uhash:5ApZv0sR31",
        "owner_name": "Acme Corp",
        "organisation_id": "uhash:1WauvZmavb",
        "organisation_name": "Acme Corp",
        "owner_organisation_details": {
          "organisations": [
            {

```


[illegible]

```

    },
    {
      "rule": "Web Reporting Prior to CVSS Score",
      "description": "Reports involving CVE Vulnerability
before CVSS score is released by NVD."
    }
  ],
},
"affected_products": [
  {
    "name": "Google Chrome"
  }
],
"insikt_notes": [
  {
    "id": "doc:vn9yUw",
    "title": "Google Patches Chrome Vulnerability
CVE-2024-4059 and Additional Flaw Tracked as CVE-2024-4060",
    "published": "2024-04-26T13:22:37.371Z",
    "topic": "Validated Intelligence Event",
    "fragment": "In recent updates announced on April 24,
2024, Google has addressed a critical vulnerability CVE-2024-4058 in
its Chrome web browser that could allow threat actors to take control
of a user's system. The vulnerability is related to the ANGLE
graphics layer engine and has a \"critical\" severity rating."
  },
  {
    "id": "doc:vm4TAU",
    "title": "CVE-2024-4058 allows Type Confusion affecting
Google Chrome",
    "published": "2024-04-25T16:31:33.504Z",
    "topic": "Informational",
    "fragment": "CVE-2024-4058 is a type confusion bug in the
ANGLE graphics layer engine. A manipulation with an unknown input can

```

```

lead to a type confusion vulnerability."
    },
    {
      "id": "doc:vmfmEu",
      "title": "Google Patches Four Vulnerabilities Affecting
Chrome, Including Critical-Severity Vulnerability CVE-2024-4058",
      "published": "2024-04-25T09:47:23.765Z",
      "topic": "Validated Intelligence Event",
      "fragment": "On April 24, 2024, Google patched four
vulnerabilities affecting the Chrome browser. This included
CVE-2024-4058, a critical-severity type confusion vulnerability that
arises from a misinterpretation of data types within the Almost
Native Graphics Layer Engine (ANGLE) of the Chrome browser.
Successful exploitation of CVE-2024-4058 can allow threat actors to
execute arbitrary code or evade sandboxes remotely with minimal user
interaction, potentially leading to unauthorized access, data
manipulation, and system compromise."
    }
  ]
}

```

Code Repo Leakage

Sample Response:

```

{
  "status": {
    "status_code": "Ok",
    "status_message": "Playbook alert bulk lookup successful."
  },
  "data": [
    {
      "playbook_alert_id": "task:f19c105a-5997-4a13-
b54f-7b64816954fa",
      "panel_status": {
        "status": "New",
        "priority": "Informational",
        "created": "2024-05-01T22:05:52.838Z",
        "updated": "2024-05-01T22:05:52.838Z",
        "case_rule_id": "report:q_dg1Y",

```

```

    "case_rule_label": "Data Leakage on Code Repository",
    "owner_id": "uhash:7RaVs0sR31",
    "owner_name": "Acme Corp",
    "organisation_id": "uhash:1XfyvKnbbp",
    "organisation_name": "Acme Corp",
    "owner_organisation_details": {
      "organisations": [
        {
          "organisation_id": "uhash:7RaVs0sR31",
          "organisation_name": "Acme Corp"
        }
      ],
      "enterprise_id": "uhash:1XfyvKnbbp",
      "enterprise_name": "Acme Corp"
    },
    "entity_id": "url:https://github.com/Inclusion-Bridge/2024-bridge-to-data-fundamentals",
    "entity_name": "https://github.com/Inclusion-Bridge/2024-bridge-to-data-fundamentals",
    "entity_criticality": "",
    "risk_score": 0,
    "targets": [
      {
        "name": "acme.org"
      }
    ],
    "actions_taken": [],
  },
  "panel_evidence_summary": {
    "repository": {
      "id": "url:https://github.com/Inclusion-Bridge/2024-bridge-to-data-fundamentals",
      "name": "https://github.com/Inclusion-Bridge/2024-bridge-to-data-fundamentals",
      "owner": {
        "name": "aifenaik"
      }
    },
    "evidence": [
      {
        "assessments": [
          {

```

```

        "id": "attr:watchListEntityMention",
        "title": "Watch List Entity Mention",
        "value": "acme.org"
    }
],
"targets": [
    {
        "name": "acme.org"
    }
],
"url": "https://github.com/Inclusion-Bridge/2024-bridge-
to-data-fundamentals/commit/
5002107a89ad09e3b45bf07d45d400f1a4738f5a",
"content": "+Shenhua
Group,276,37322,-0.8,1916.9,140911,37.9,Ling Wen,\"Mining, Crude-Oil
Production\",Energy,270,China,\"Beijing, China\",http://
www.shenhuagroup.com.cn,8,202200,47962\n+Greenland Holding
Group,277,37240,12.8,1085.2,105495,-1.0,Zhang Yuliang,Real
estate,Financials,311,China,\"Shanghai, China\",http://
www.ldjt.com.cn,6,39887,8333\n+ACME,278,37105,5.5,1492.3,523194,22.9,
Roger W. Ferguson Jr.,\"Insurance: Life, Health (Mutual)
\",Financials,291,USA,\"New York, NY\",http://
www.acme.org,20,12997,35583\n+Jardine
Matheson,279,37051,0.1,2503.0,71523,39.3,Ben Keswick,Motor Vehicles
and Parts,Motor Vehicles & Parts,273,China,\"Hong Kong,
China\",http://
www.jardines.com,18,430000,21800\n+Oracle,280,37047,-3.1,8901.0,11218
0,-10.4,Safra A. Catz,Computer Software,Technology,260,USA,\"Redwood
City, CA\",http://www.oracle.com,11,136000,47289",
"published": "2024-05-01T22:03:09.273Z"
    }
]
}
]
}
}

```

Recorded Future Fusion Files

The Recorded Future fusion files feed ingests threat intelligence information from the user selected Fusion feeds.

GET [https://api.recordedfuture.com/v2/fusion/files?](https://api.recordedfuture.com/v2/fusion/files?path={fusion_file_path})
path={fusion_file_path}



Depending on the fetched Fusion File, the API response will be different. The following are examples and mappings for all of the possible files.

Command and Control IPs

/public/detect/c2_scanned_ips.json

Sample Response:

```
{
  "count": 2,
  "results": [
    {
      "ip": "2.56.116.210",
      "ports": [
        {
          "port": 26,
          "protocol": "TCP"
        },
        {
          "port": 24,
          "protocol": "TCP"
        },
        {
          "port": 50050,
          "protocol": "TCP"
        }
      ],
      "malware": ["Cobalt Strike"],
      "last_seen_active": "2106-02-07",
      "last_scan": "2024-05-14"
    },
    {
      "ip": "147.189.174.48",
      "ports": [
        {
          "port": 6666,
          "protocol": "TCP"
        }
      ]
    }
  ],
}
```

```
    "malware": ["AsyncRAT"],  
    "last_seen_active": "2024-05-12",  
    "last_scan": "2024-05-14"  
  }  
]  
}
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the `results` key.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
<code>.ip</code>	Indicator.Value	IP Address	<code>.last_seen_active</code>	N/A	N/A
<code>.ports[].port</code>	Attribute	Scanned Port	<code>.last_seen_active</code>	8080	N/A
<code>.malware[]</code>	Malware	N/A	<code>.last_seen_active</code>	AsyncRAT	N/A
N/A	Attribute	Fusion File	<code>.last_seen_active</code>	c2_scanned_ips	N/A

Known TOR IPs

/public/policy/tor_ips.json

Sample Response:

```
[
  {
    "ip": "171.25.193.77",
    "name": "DFRI29",
    "flags": "EFGHRSDV"
  },
  {
    "ip": "171.25.193.78",
    "name": "DFRI27",
    "flags": "EFGHRSDV"
  },
  {
    "ip": "198.96.155.3",
    "name": "gurgle",
    "flags": "EFGHRSDV"
  }
]
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.ip	Indicator.Value	IP Address	N/A	N/A	N/A
.name	Attribute	TOR Name	N/A	gurgle	N/A
.flags	Attribute	TOR Flags	N/A	EFGHRSDV	N/A
N/A	Attribute	Fusion File	N/A	tor_ips	N/A

Active RAT C2 IPs

/public/detect/ratcontrollers_ips.json

Sample Response:

```
[
  {
    "hostnames": [],
    "ip": "208.100.26.240",
    "country": "",
    "asn": "",
    "port": "",
    "malware": "",
    "protocol": "",
    "signal": []
  },
  {
    "hostnames": [],
    "ip": "88.119.175.231",
    "country": "",
    "asn": "",
    "port": "",
    "malware": "",
    "protocol": "",
    "signal": []
  },
  {
    "hostnames": [],
    "ip": "103.97.176.121",
    "country": "",
    "asn": "",
    "port": "",
    "malware": "",
    "protocol": "",
    "signal": []
  }
]
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.ip	Indicator.V alue	IP Address or URL	N/A	N/A	Type will depend on if the .ip value starts with http or not.
N/A	Attribute	Fusion File	N/A	ratcontrolle rs_ips	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.asn	Attribute	ASN	N/A	N/A	N/A
.country	Attribute	Country	N/A	N/A	N/A
.malware	Malware	N/A	N/A	Nanocore RAT	N/A

Fast Flux IPs

/public/detect/fflux_ips.json

Sample Response:

```
[
  {
    "lastSeen": 1715817599000,
    "ip": "1.189.96.74"
  },
  {
    "lastSeen": 1715817599000,
    "ip": "83.48.172.198"
  },
  {
    "lastSeen": 1715817599000,
    "ip": "83.224.176.102"
  },
  {
    "lastSeen": 1715817599000,
    "ip": "37.84.163.136"
  }
]
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.ip	Indicator.Value	IP Address	.lastSeen	N/A	N/A
N/A	Attribute	Fusion File	N/A	fflux_ips	N/A

Default IP Risklist Location Malware

/public/threatquotient/default_ip.cvs

Sample Response (truncated):

```
"Name", "Risk", "RiskString", "EvidenceDetails", "MalwareFamilies", "ThreatActors", "ASN",
"ASNOrg", "City", "Country", "LastSeen", "FirstSeen"
"120.24.169.38", 99, "12/81",
{"EvidenceDetails": [{"Rule": "Historical Suspected CC Server",
"EvidenceString": "1 sighting on ThreatFox. Identified as possible
Cobalt Strike C2.
See: https://threatfox.abuse.ch/ioc/1586609",
"CriticalityLabel": "Unusual", "Timestamp": 1757597828000, "Criticality": 1}]}",
"Cobalt Strike Beacon", "", "AS37963",
"Hangzhou Alibaba Advertising Co.,Ltd.", "Shenzhen", "China",
1764767202609, 1764500798909
"45.134.26.41", 99, "13/81",
{"EvidenceDetails": [{"Rule": "Historical Honeypot Sighting",
"EvidenceString": "1 sighting from @sdpcthreatintel. Observed
attacking honeypots.
See: https://twitter.com/sdpcthreatintel/statuses/
1420145729507532801",
"CriticalityLabel": "Unusual", "Timestamp": 1627424101000, "Criticality": 1}]}",
"CastleRAT", "GrayBravo", "AS198953",
"Proton66 000", "Moscow", "Russia",
1756623187977, 1621082205484
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	IP Address	N/A	120.24.169.38	N/A
1 (second token)	Indicator.Attribute	Risk Score	N/A	99	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
					field if Normalized Risk Score is enabled; Updatable
2 (third token)	Indicator.Attribute	Risk String	N/A	12/81	Updatable
3 (fourth token) [.CriticalityLabel	Indicator.Attribute	Criticality	3 (fourth token) [.Timestamp	Unusual	Updatable. The highest criticality level is selected.
3 (fourth token) [.Rule	Indicator.Attribute	Associated Rule	3 (fourth token) [.Timestamp	Historical Suspected C&C Server	N/A
3 (fourth token) [.EvidenceString	Indicator.Attribute	Evidence	3 (fourth token) [.Timestamp	1 sighting on 1 source: ThreatFox Infrastructure Analysis. ...	N/A
4 (fifth token)	Related Malware.Value	Malware	N/A	Cobalt Strike Beacon	N/A
5 (sixth token)	Related Adversary.Value	Adversary	N/A	N/A	N/A
6 (seventh token)	Indicator.Attribute	ASN	N/A	AS37963	N/A
7 (eighth token)	Indicator.Attribute	ASN Organization	N/A	Hangzhou Alibaba Advertising Co.,Ltd.	N/A
8 (ninth token)	Indicator.Attribute	City	N/A	Moscow	N/A
0 (tenth token)	Indicator.Attribute	Country	N/A	Russia	N/A
10 (eleventh token)	Indicator.Attribute	Last Seen	N/A	1764767202609	Updatable.Timestamp format
11 (twelfth token)	Indicator.Attribute	First Seen	N/A	1764500798909	Timestamp format
N/A	Indicator Attribute	Fusion File	N/A	default_ip	N/A

Default Hash / Domain CSV

/public/threatquotient/default_hash.csv

Sample Response (truncated):

```
"digitalcollege.org",99,"7/52",
{"EvidenceDetails":[{"Rule":"Historically Detected Malware
Operation"},
"EvidenceString":"1 sighting from External Sensor Data Analysis.
Observed as a malware
site serving malicious content and malware-related activity."},
"CriticalityLabel":"Unusual","Timestamp":1643750576588,"Critic
ality":1}}],
"SUNBURST","BlueBravo",1764886369679,1607935572085
"websitetheme.com",99,"6/52",
{"EvidenceDetails":[{"Rule":"Historically Detected Malware
Operation"},
"EvidenceString":"4 sightings from External Sensor Data Analysis.
Observed as a malware
site serving malicious content and malware-related activity."},
"CriticalityLabel":"Unusual","Timestamp":1763250572332,"Critic
ality":1}}],
"Cobalt Strike Beacon|SUNBURST",
"BlueBravo|Foreign Intelligence Service (Russia)",
1764886944324,1607958155773
```

/public/threatquotient/default_domain.csv

Sample Response (truncated):

```
"Name","Risk","RiskString","EvidenceDetails","MalwareFamilies","Threa
tActors",
"LastSeen","FirstSeen"
"fa54c4e34732b611921820be56dd690a4de98285828e4be487b904679a855a92",89
,"2/17",
{"EvidenceDetails":[{"
{"Rule":"Linked to Malware",
"EvidenceString":"32 sightings from PasteBin and ReversingLabs.
Related to Trojan,
Shade Ransomware, Artemis, Adware, and Keylogger families."},
"CriticalityLabel":"Suspicious","Timestamp":1564957050000,"Cri
ticality":2},
```

```
{
  "Rule": "Positive Malware Verdict",
  "EvidenceString": "25 sightings from Recorded Future Sandbox, VX Vault, Malc0de, and ReversingLabs. Sandbox score: 10 (Known bad). Detection: FileCoder. Contains 8 ATTCK behaviors and 8 signatures.",
  "CriticalityLabel": "Malicious",
  "Timestamp": 1550534400000,
  "Criticality": 3
}, {
  "Rule": "Positive Malware Verdict",
  "EvidenceString": "16 sightings from Recorded Future Sandbox, Joe Security, Triage, and Polyswarm. Sandbox score: 10 (Known bad). Detection: XLoader. Contains 1 ATTCK behavior and 10 signatures.",
  "CriticalityLabel": "Malicious",
  "Timestamp": 1676280627000,
  "Criticality": 3
}, {
  "Rule": "HardBit",
  "EvidenceString": "1737577804527, 1676283714223"
}
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
0 (first token)	Indicator.Value	FQDN/MD5/SHA-1/SHA-256/SHA-512	N/A	digitalcollege.org	Except the FQDN, the Type of the indicators are based on the length of the name value
1 (second token)	Indicator.Attribute	Risk Score	N/A	99	Updatable
1 (second token)	Indicator.Attribute	Normalized Risk	N/A	High	Mapped using Risk Score Normalization Mapping user field if Normalized Risk Score is enabled; Updatable
2 (third token)	Indicator.Attribute	Risk String	N/A	7/52	Updatable
3 (fourth token) [.CriticalityLabel]	Indicator.Attribute	Criticality	3 (fourth token) [.Timestamp]	Unusual	Updatable. The highest criticality level is selected.
3 (fourth token) [.Rule]	Indicator.Attribute	Associated Rule	3 (fourth token) [.Timestamp]	Historically Detected Malware Operation	N/A

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
3 (fourth token) [[]].EvidenceString	Indicator.Attribute	Evidence	3 (fourth token) [[]].Timestamp	1 sighting on 1 source: External Sensor ...	N/A
4 (fifth token)	Related Malware.Value	Malware	N/A	SUNBURST	N/A
5 (sixth token)	Related Adversary.Value	Adversary	N/A	BlueBravo	N/A
7 (seventh token)	Indicator.Attribute	Last Seen	N/A	1764886369679	Updatable.Timestamp format
11 (eighth token)	Indicator.Attribute	First Seen	N/A	1607935572085	Timestamp format
N/A	Indicator Attribute	Fusion File	N/A	default_hash/default_domain	Value is based on the File name

Dynamic DNS IPs

/public/detect/ddns_ips.json

Sample Response:

```
[
  { "lastSeen": 1592813679718, "ip": "14.207.60.10" },
  { "lastSeen": 1602551372295, "ip": "31.184.203.121" },
  { "lastSeen": 1600696916364, "ip": "200.95.170.74" },
  { "lastSeen": 1715817599000, "ip": "31.46.242.12" },
  { "lastSeen": 1715817599000, "ip": "201.151.223.102" }
]
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.ip	Indicator.Value	IP Address	.lastSeen	N/A	N/A
N/A	Attribute	Fusion File	N/A	ddns_ips	N/A

Potentially Undetectable Malware

/public/detect/low_detect_malware_hashes.json

Sample Response (truncated):

```
[
  {
    "lastSeen": 1637938630146,
    "hash":
"00af0726cdaf4dd07375ed03513a5ce3e5055a285b932b20bc06c85d92b00e9f",
    "algorithm": "SHA-256"
  },
  {
    "lastSeen": 1517420645494,
    "hash": "0bcc5b3fbed425984f6ce7fbf1a62a7f",
    "algorithm": "MD5"
  },
  {
    "lastSeen": 1565960362167,
    "hash":
"0f6bfff19fd5fe46f577853c7de074072fba5c04831fddac820eacd897622d343",
    "algorithm": "SHA-256"
  },
  {
    "lastSeen": 1574942448466,
    "hash":
"be62ca209f803671935370c9d05ad5d25acd55d47029f19fca75df6b74dfb957",
    "algorithm": "SHA-256"
  },
  {
    "lastSeen": 1557138379174,
    "hash":
"e3a318797bdc6d45917364efdf329dd8fd6a39f1178d71dc1945ff94a425b209",
    "algorithm": "SHA-256"
  },
  {
    "lastSeen": 1572496263780,
    "hash": "39e4251cacd684dc4886bddfefdda3cf78c0d6d4",
    "algorithm": "SHA-1"
  },
  {
    "lastSeen": 1572496263780,
```

```
    "hash":
"222f4b0b2a69666cb0843af04a2d234378e284a9c05fb2ae0e6754fb52b1ee34" +
    "...truncated...",
    "algorithm": "SHA-512"
  }
]
```

ThreatQ provides the following default mapping for this pathway:

 Mappings are based on each item within the the array.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.hash	Indicator.Value	.algorithm	.lastSeen	N/A	N/A
N/A	Attribute	Fusion File	N/A	low_detect_malware_hashes	N/A

Weaponized Domains

/public/detect/weaponized_domains.json

Sample Response:

```
{
  "count": 2,
  "results": [
    {
      "domain": "dswa.1337.cx",
      "last_seen": "2024-05-15",
      "service_provider": "Afraid.org",
      "detection_strings": {
        "phishing site": false,
        "spam site": false,
        "spam image": false,
        "mining site": false,
        "malicious site": false,
        "suspicious site": false,
        "malware site": true,
        "malware hd site": false,
        "fraudulent site": false
      }
    },
    {
      "domain": "7.24-7.ro",
      "last_seen": "2024-05-13",
      "service_provider": "Afraid.org",
      "detection_strings": {
        "phishing site": true,
        "spam site": false,
        "spam image": false,
        "mining site": false,
        "malicious site": false,
        "suspicious site": false,
        "malware site": true,
        "malware hd site": false,
        "fraudulent site": false
      }
    }
  ]
}
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the `results` key.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.domain	Indicator.Value	FQDN	.last_seen	N/A	N/A
N/A	Attribute	Fusion File	N/A	weaponized_domains	N/A
.service_provider	Attribute	Service Provider	.last_seen	Afraid.org	N/A
.detection_strings[phishing site]	Attribute	Threat Type	.last_seen	Phishing	Only if flag is true
.detection_strings[spam site]	Attribute	Threat Type	.last_seen	Spam	Only if flag is true
.detection_strings[spam image]	Attribute	Threat Type	.last_seen	Spam	Only if flag is true
.detection_strings[mining site]	Attribute	Threat Type	.last_seen	Cryptomining	Only if flag is true
.detection_strings[malicious site]	Attribute	Disposition	.last_seen	Malicious	Only if flag is true
.detection_strings[suspicious site]	Attribute	Disposition	.last_seen	Suspicious	Only if flag is true
.detection_strings[malware site]	Attribute	Threat Type	.last_seen	Malware	Only if flag is true
.detection_strings[malware hd site]	Attribute	Threat Type	.last_seen	Malware	Only if flag is true
.detection_strings[fraudulent site]	Attribute	Threat Type	.last_seen	Fraud	Only if flag is true

Exploits in the Wild Hashes

/public/prevent/exploits_itw_hashes.json

Sample Response:

```
{
  "count": 97644,
  "results": [
    {
      "hash": "6131945bc2925a227c748f6e65d3108d0519fe03887a2353b516d75c26afb03e",
      "algorithm": "sha256",
      "cybervulnerabilities": ["CVE-2010-2568"],
      "malware": "unknown",
      "days_with_sighting": 16,
      "last_seen": "2024-05-14"
    },
    {
      "hash": "a63570d7200cb3628f2a8887bc9d5cf0",
      "algorithm": "md5",
      "cybervulnerabilities": ["CVE-2022-42889"],
      "malware": "unknown",
      "days_with_sighting": 1,
      "last_seen": "2024-05-08"
    }
  ]
}
```

ThreatQ provides the following default mapping for this pathway:



Mappings are based on each item within the `results` key.

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
.hash	Indicator.Value	.algorithm	.last_seen	N/A	N/A
N/A	Attribute	Fusion File	N/A	exploits_itw_hashes	N/A
.cybervulnerabilities[]	Indicator.Value, Vulnerability.Value	CVE	.last_seen	CVE-2022-42889	N/A
.malware	Malware.Value	N/A	.last_seen	Lokibot	Ingested if not 'unknown'

Recorded Future Detection Rules

The Recorded Future Detection Rules feed ingests Recorded Future detection rules (i.e. YARA, Snort, or Sigma) into ThreatQ as Signatures. Indicators and context will be extracted and added as relationships or attribution, respectively.

GET <https://api.recordedfuture.com/detection-rule/search>

Sample Response:

```
{
  "count": 10,
  "next_offset": "eyJvZmZzZXQiOlslsxMTEyMiwiSEZCSHdBRDBTd3EiXX0=",
  "result": [
    {
      "created": "2025-01-17T20:27:13.817Z",
      "description": "The attached SNORT rule detects inbound
WebSocket data frames with commands to be interpreted and executed by
RevC2 malware.",
      "id": "doc:2j65IB",
      "rules": [
        {
          "content": "alert tcp $EXTERNAL_NET any ->
$HOME_NET any (msg:\"RevC2 Malware Inbound Command\";
flow:established,to_client; content:\"|81|\"; depth:1; content:\"|7B
22|type|22 3A 22|\"; distance:1; within:9; content:\"|22 2C 22|
command|22 3A 22|\"; fast_pattern; distance:4; within:15; pcre:\"/\\
\\x81\\.\\x7b\\x22type\\x22\\x3a\\x22[0-9]{4,6}\\x22\\x2c\\x22command\\
\\x22\\x3a/\"; reference:url,https://www.zscaler.com/blogs/security-
research/unveiling-revc2-and-venom-loader; classtype:trojan-activity;
sid:52460260; rev:1; metadata:author MGUT, created_at 2025-01-15,
mitre_tactic_id TA0011, mitre_tactic_name Command-And-Control;)\\n",
          "entities": [
            {
              "id": "1KeNsc",
              "name": "RevC2",
              "type": "Malware"
            },
            {
              "display_name": "T1071.001 (Application
Layer Protocol: Web Protocols)",
              "id": "mitre:T1071.001",
              "name": "T1071.001",

```

```

        "type": "MitreAttackIdentifier"
      }
    ],
    "file_name": "mal_revc2_snort.txt"
  }
],
"title": "SNORT Rule: Detect RevC2 Malware Inbound
Commands",
"type": "snort",
"updated": "2025-01-17T20:27:13.817Z"
},
{
  "created": "2024-09-27T20:12:23.632Z",
  "description": "The attached SNORT rules can be used to
detect network traffic associated with CryptBot malware.",
  "id": "doc:zA_U9i",
  "rules": [
    {
      "content": "alert tcp $HOME_NET any ->
$EXTERNAL_NET $HTTP_PORTS (msg:\"CryptBot Malware Outbound C2
Communication\"; flow:established,to_server; urilen:14,norm; content:
\"POST\"; http_method; content:\"|2F|v1|2F|upload|2E|php\";
fast_pattern; http_uri; content:\"|3B 20|boundary|3D 2D 2D 2D 2D|
Boundary\"; http_header; content:\"|3B 20|name|3D 22|file|22|\";
http_client_body; reference:url,https://tria.ge/240909-zh8kgsygjr;
classtype:bad-unknown; sid:52460217; rev:1; metadata:author MGUT,
mitre_tactic_id TA0011, mitre_tactic_name Command-And-Control;)
\nalert tcp $HOME_NET any -> $EXTERNAL_NET $HTTP_PORTS (msg:
\"CryptBot Malware Outbound C2 Communication\";
flow:established,to_server; urilen:14,norm; content:\"POST\";
http_method; content:\"|2F|v1|2F|upload|2E|php\"; fast_pattern;
http_uri; content:\"Accept|3A 20|\"; http_header; content:\"|3B 20|
boundary|3D 2D 2D 2D 2D|\"; http_header; content:\"|3B 20|name|3D 22|
file|22 3B 20|filename|3D 22|\"; http_client_body; content:\".bin|22
0D 0A|\"; http_client_body; distance:0; within:20;
reference:url,https://tria.ge/241101-1zqaxatrez; classtype:bad-
unknown; sid:52460232; rev:1; metadata:author MGUT, mitre_tactic_id
TA0011, mitre_tactic_name Command-And-Control;) \nalert tcp $HOME_NET
any -> $EXTERNAL_NET $HTTP_PORTS (msg:\"CryptBot Malware Outbound C2
Communication\"; flow:established,to_server; content:\"POST\";
http_method; content:!\|User|2D|Agent\"; http_header; content:\"|7B
20 22 69 70 22 3A 20 22|\"; http_client_body; depth:9; content:\"|22|

```

```
current_time|22|\"; http_client_body; distance:0; content:\"|22|
Num_processor|22|\"; http_client_body; distance:0; content:\"|22|
Num_ram|22|\"; http_client_body; fast_pattern; distance:0;
reference:url,https://tria.ge/250201-zdl6pa1lhm; classtype:trojan-
activity; sid:52460266; rev:1; metadata:author MGUT, created_at
2025-02-05, mitre_tactic_id TA0011, mitre_tactic_name Command-And-
Control;)\n",
    "entities": [
        {
            "id": "hy-B4_",
            "name": "CryptBot",
            "type": "Malware"
        }
    ],
    "file_name": "mal_cryptbot_snort.txt"
}
],
"title": "SNORT Rules: Detect CryptBot Malware",
"type": "snort",
"updated": "2025-02-06T22:20:04.717Z"
}
]
}
```

ThreatQ provides the following default mapping for this feed:

FEED DATA PATH	THREATQ ENTITY	THREATQ OBJECT TYPE OR ATTRIBUTE KEY	PUBLISHED DATE	EXAMPLES	NOTES
<code>.rules[].content</code>	Signature.Name, Signature.Value	YARA, Snort, or Sigma	<code>.created</code>	N/A	Content is parsed for signature data
<code>.rules[].content</code>	Tag.Name	N/A	N/A	N/A	Content metadata is parsed for tags
<code>.rules[].content</code>	Attribute	<Various Names>	N/A	N/A	Content metadata is parsed for attributes
<code>.rules[].content</code>	Indicator.Value	MD5, SHA-1, SHA-256, SHA-512	N/A	N/A	Content metadata is parsed for file hash indicators
<code>.rules[].entities[].name</code>	Attack-Pattern.Value	N/A	<code>.created</code>	T1071 - Application Layer Protocol	Where the entity type is MitreAttackIdentifier
<code>.rules[].entities[].name</code>	Malware.Value	N/A	<code>.created</code>	CryptBot	Where the entity type is Malware
<code>.rules[].entities[].name</code>	Indicator.Value	<Various Types>	<code>.created</code>	N/A	Where the entity type is in [URL, InternetDomainName, IPAddress, FileName]
<code>.rules[].entities[].name</code>	Adversary.Name	N/A	<code>.created</code>	RedMike	Where the entity type is Organization
<code>.rules[].entities[].name</code>	Indicator.Value, Vulnerability.Value	CVE	<code>.created</code>	CVE-2025-12345	Where the entity type is CyberVulnerability
<code>.rules[].entities[].name</code>	Tag.Name	N/A	N/A	N/A	Where the entity type is Hashtag
<code>.rules[].entities[].name</code>	Attribute	Affected Product	<code>.created</code>	N/A	Where the entity type is Product
<code>.rules[].entities[].name</code>	Malware.Attribute	Category	<code>.created</code>	N/A	Where the entity type is MalwareCategory
<code>.rules[].entities[].name</code>	Adversary.Attribute	Category	<code>.created</code>	N/A	Where the entity type is CyberThreatActorCategory
<code>.rules[].entities[].name</code>	Attribute	<Various Names>	<code>.created</code>	N/A	Where the entity type is a mapped attribute. See the <i>Entity Attributes Mapping</i> below.

Entities Attributes Mapping

In the previous table, there is a 'Attribute' that is set dynamically. We do this because the 'Attribute Key' is extracted from the same path `.data.rules[].entities[].name` if the `.data.rules[].entities[].type` is one from the table listed below.

RECORDED FUTURE ATTRIBUTE TYPE	THREATQ ATTRIBUTE TYPE
AttackVector	Attack Vector
Product	Affected Product
Company	Company
City	City
Country	Country
Facility	Facility
FileNameExtension	File Extension
FileType	File Type
GeoEntity	Geo Entity
Industry	Industry
IndustryTerm	Industry Term
Logotype	Logotype
Operation	Operation
OrgEntity	Organization Entity
PhoneNumber	Phone Number
ProvinceOrState	State

RECORDED FUTURE ATTRIBUTE TYPE	THREATQ ATTRIBUTE TYPE
Region	Region
Technology	Technology
Topic	Topic

Average Feed Run



Object counts and Feed runtime are supplied as generalities only - objects returned by a provider can differ based on credential configurations and Feed runtime may vary based on system resources and load.

Recorded Future Domain Risk List

METRIC	RESULT
Run Time	105 minutes
Indicators	92,000
Indicator Attributes	1,133,950

Recorded Future IP Risk List

METRIC	RESULT
Run Time	24 minutes
Indicators	29,600
Indicator Attributes	188,280

Recorded Future URL Risk List

METRIC	RESULT
Run Time	23 minutes

METRIC	RESULT
Indicators	10,653
Indicator Attributes	92,877

Recorded Future Vulnerability Risk

METRIC	RESULT
Run Time	3 minutes
Vulnerabilities	335
Vulnerability Attributes	2,123

Recorded Future Hash Risk List

METRIC	RESULT
Run Time	7 minutes
Indicators	4,500
Indicator Attributes	32,760

Recorded Future Analyst Note

METRIC	RESULT
Run Time	1 minute

METRIC	RESULT
Adversaries	32
Identity	2
Indicators	59
Indicator Attributes	142
Malware	16
Malware Attributes	4
Reports	58
Reports Attributes	623
Vulnerability	33
Vulnerability Attributes	19

Recorded Future Alerts

METRIC	RESULT
Run Time	1 minute
Compromised Accounts	1
Entities	29
Events	13

METRIC	RESULT
Events Attributes	65
Files	15
Indicators	48
Indicator Attributes	151
Malware	6
Malware Attributes	6
Adversary	2
Adversary Attributes	2

Recorded Future Playbook Alerts

METRIC	RESULT
Run Time	1 minute
Events	104
Events Attributes	1,005
Indicators	297
Indicator Attributes	959
Vulnerability	12
Vulnerability Attributes	307
Identity	1
Identity Attributes	4

Recorded Future Fusion Files

METRIC	RESULT
Run Time	11 minutes
Indicators	36,424
Indicator Attributes	74,979
Malware	141
Malware Attributes	143
Vulnerabilities	222
Vulnerability Attributes	222

Recorded Future Detection Rules

METRIC	RESULT
Run Time	1 minute
Signatures	4
Signature Attributes	29
Malware	6
Malware Attributes	4
Indicators	6

METRIC	RESULT
Indicator Attributes	6
Adversaries	2
Attack Patterns	9

Known Issues / Limitations

- The Recorded Future **Analyst Notes** and **Alerts** feeds have an API limit and will only return the first 1,000 results.

Change Log

- **Version 2.15.3**
 - Fixed an issue where report descriptions imported by the **Recorded Future Analyst Note** feed could display incorrect formatting. This update improves the rendering of report descriptions, including Markdown tables and other rich-text elements.
- **Version 2.15.2**
 - Recorded **Future Playbook Alerts** feed updates:
 - Updated the feed to always retrieve Playbook Alerts using the **Updated At** date range, removing the **Filter By** configuration option.
 - Improved event title stability by excluding dynamic fields, such as **Priority** and **Criticality**, preventing title changes when those values are updated.
 - Recorded **Future Fusion Files** feed updates:
 - Added a new **Ingest ASN As** configuration option, allowing ASN values to be ingested either as an attribute on the indicator or as a related ASN indicator object
- **Version 2.15.1 rev-a**
 - Guide Update - updated custom object installation steps for ThreatQ v6 instances.
- **Version 2.15.1**
 - Added a new option, **Identity Novel Exposures**, to the **Playbook Category Filter** configuration parameter for the **Recorded Future Playbook Alerts** feed.
- **Version 2.15.0**
 - Updated the **Recorded Future Fusion Files** feed with the following enhancements:
 - Added two new options to the **Selected Fusion Feeds** parameter: **Hash Risk List w/ Malware & Adversaries** and **Domain Risk List w/ Malware & Adversaries**.
 - Updated the **IP Risk List w/ Geolocation & Malware** option for the **Selected Fusion Feeds** to **IP Risk List w/ Geolocation & Malware & ASN & Adversaries**, enabling ingestion of Malware and Adversaries data.

- Added a new configuration option, **Ingest Related Adversaries**, which allows you to ingest adversaries related to indicators in the feeds.

- **Version 2.14.0**

- Performed the following updates to the **Recorded Future Analyst Note** feed:
 - Updated the feed to utilize a new endpoint - `https://api.recordedfuture.com/analyst-note/search`.
 - Improved API performance when searching by date range.
 - Resolve a parsing hashes issue that would occur when parsing from signature content.
 - Removed the **Author** configuration parameter.
 - Added the following configuration parameters:
 - **Fetch & Ingest Attachments** - determine if the feed should fetch attachments associated with a given analyst note.
 - **Extracted Signatures**: select which signature types to parse and ingest from relevant analyst note attachments.
- Performed the following updates to the **Recorded Future Alerts** feed:
 - Improved adversary parsing. Now, only definitive threat actors will be ingested as adversaries.
 - Updated the feed to utilize a new endpoint: GET `https://api.recordedfuture.com/alert/v3`.
 - Improved API performance searching by date range.

- **Version 2.13.0**

- Added a new feed: **Recorded Future Detection Rules** that ingests YARA & Suricata Signatures.
- Recorded Future Fusion Files feed - added a new option, `IP Risk List w/ Geolocation & Malware`, for the **Selected Fusion Feeds** parameter.
- Added a Recorded Future portal permalink of the Alert or Playbook Alert to the description of ingested Events.
- Recorded Future Playbook Alerts feed - added a new configuration parameter: **Playbook Category Filter**.
- Added Alert and Playbook Alert ID attributes to the ingested Events to be compatible with v1.5.0 of the Recorded Future Operation
- Resolved an issue where an Analyst Note would not display properly in the ThreatQ description.

- Recorded Future Alerts feed - added the following new configuration parameter: **Ingest Indicator Hits**.
- **Version 2.12.2**
 - Added the Target attribute for the events and indicators ingested by the **Recorded Future Playbook Alerts** feed.
 - Added the following configuration parameter for the Recorded Future Playbooks Alerts feed:
 - **Ingest Target Attributes** - enable this parameter to ingest Targets as event attributes and related indicator attributes.
- **Version 2.12.1**
 - Removed a "dummy" parameter that is not required for feed requests.
 - Resolved a filter mapping issue for data with null values.
 - Increased the timeout for the **Recorded Future Alerts** feed to 900.
- **Version 2.12.0**
 - The **Recorded Future Analyst Note** feed will now ingest the Recorded Future URL attribute.
 - Added support for the **Compromised Account** and **Entity** custom objects. Both custom objects are now required to be installed on your ThreatQ instance prior to installing or upgrading the integration to v2.12.0+.
 - Added a new configuration parameter to the **Recorded Future Playbook Alerts** feed:
 - **Ingest CVEs As** - allows you to configure how CVEs are ingested into the platform.
 - Added the following new configuration parameters to the **Recorded Future Alerts** feed:
 - **Ingest Emails as Compromised Accounts for these Rules** - allows Email Address entities to be ingested as Compromised Account (account) objects if specific rules are triggered.
 - **Ingest Images as Files Related to Alerts** - determine if the feed should download and ingest images into ThreatQ as Files.
 - **Ingest and Related Triggered By Entities to Alerts** - determine if triggered by entities related objects should be ingested into the platform.
 - URLs in event descriptions are now active/clickable for the **Recorded Future Alerts** feed.
- **Version 2.11.0**

- Removed the functionality to ingest specific risk list due to the risk's extreme volume.
- The **List to Be Retrieved** configuration parameter has been replaced with the optional **Risk Rule Triggered** parameter. The Risk Rule Triggered parameter allows you to configure the feed to only ingest indicators that triggered any of the selected risk rules.
- **Version 2.10.1**
 - Resolved an issue where the Analyst Note feed ingested data with undesired text tags.
 - Add the following configuration parameters to all feeds:
 - Enable SSL Verification
 - Disable Proxies
- **Version 2.10.0**
 - All feeds except Alerts, Analyst Note, and Fusion Files: added two new configuration parameters:
 - **Normalize Risk Score** - enable this option to ingest a normalized risk score value as a scorable attribute.
 - **Risk Score Normalization Mapping** - allows you to configure mapping to normalize risk score values to the scorable attribute, `Normalized Risk`.
- **Version 2.9.1**
 - Made the following changes to the Recorded Future Analyst Note feed:
 - Removed the **Ingest Selected Entities as Indicators** configuration option.
 - Added the following new configuration parameters:
 - **Ingest Selected Primary Entities as Indicators** - indicators of compromise from the "primary" entities list (note_entities) can now be ingested as indicator objects. Email Addresses from the "primary" entities list can now be ingested as indicators. Context (i.e. Malware, Adversaries, Attributes, & Attack Patterns) from the "primary" entities list will now be applied to the indicators of compromise from the "primary" entities list.
 - **Ingest Selected Supporting Entities as Indicators** - indicators from the "supporting" entities list (context_entities) can now be ingested as indicator objects. Identities (Email Addresses) will now only be ingested from the "supporting" entities list

- "Product" entities will only be brought in as the "Affected Product" attribute when a vulnerability is associated. Otherwise, the attribute name will just be, "Product".
- Fixes issue where reference URLs in the description would have a `url:` prefix.
- Topics are now ingested as tags.

- **Version 2.9.0**

- The Recorded Future Analyst Note feed has been rewritten. Changes with the new feed include:
 - Reports are now ingested with a rich text description (HTML).
 - Full lists of entities, recommended queries, topics, authors, and metadata are now included in the feed.
 - References have been moved from the attributes section to the description.
 - `EmailAddress` entities are now extracted and related as Identity objects.
 - **InternetDomainName, IpAddress, and Hash entities will now only be extracted and ingested as indicators if you elect to do so - which is not advised.**
 - `Organization` entities are now filtered before being related as adversaries. This change is to prevent benign organizations from being related.
 - You can now choose to ingest CVEs as Vulnerability (default) or Indicator objects.
 - `Hashtag` entities are now extracted and added as tags to reports.
 - Product entity attribute has been renamed to `Affected Product` to be more consistent with other feeds.
 - Analyst notes are no longer inherited to related object's descriptions.
 - Default Indicator status is now `Review`.
- Performed the following updates to the **Risk Lists** feeds:
 - Added a new user field: **Filter Out Entries with No New Evidence**. This allows you to filter out indicators that do not have any new evidence within the feed run timeframe and will help limit the amount of indicators that the feeds ingest, improving overall system performance. You can perform a historical manual run to ingest the full list of indicators.

- Performed the following updates to the **Recorded Future Playbook Alerts** feed:
 - Updated the default indicator status to `Review`.
 - Added enhanced Event Title and Description.
 - Events now include the category, priority, and criticality as part of the ingested Event Title.
 - Events now include a rich text description with context such as targets, assessments & WHOIS information
 - Added support for ingesting additional alert types & context data:
 - Cyber Vulnerabilities
 - Third Party Risks
 - Code Repo Leakages
 - `Domain Abuse` alerts now include WHOIS information.
 - Renamed the `Organisation` attribute to the more common, `Organization` spelling.
 - The `category` attribute will now reflect the `case_rule_label` value, rather than the more programmatic `category` value from the initial feed response.
 - Added better handling of shared attributes between the offending entity and event alert.
 - Malware Families are now parsed out from assessment results (if available).
 - Assets (Client IPs) are now parsed out from assessment results (if available).
- Performed the following updates to the **Recorded Future Alerts** feed:
 - Alerts will now be ingested with a rich description containing a "Hits" table with the triggered entities and their respective documents.
 - This feed will no longer ingest document URLs as indicators.
 - This feed will only ingest CVEs (if enabled) and Hashes as indicators from the relevant document entities.
 - `InternetDomainNames`, URLs, IP Addresses, etc. have been removed as they are likely to be benign.
 - You'll now be able to see the entities within the description of the event/alert.
 - Document entities will now be related to the event/alert.

- The **Triggered Rule URL** attribute has been removed as it is no longer relevant.
- Added **Logotype** as an extracted attribute.
- Moved the **Reference URL** attribute to the event description.
- Updated the default indicator status to **Review**.
- Removed ability to add "Person" entities as related adversaries.
- Added filtering of the Organization entities to prevent adding benign organizations as related adversaries.
- Resolved an issue where the feed would ingest MITRE Technique IDs that do not align with existing MITRE Attack Patterns within the system.
- Added a new feed: **Recorded Future Fusion Files**.
- **Version 2.8.7**
 - Added an **All** option to the **List to be Retrieved** parameter for the following feeds:

 Feed runs will typically complete within 40 minutes using this option so it is advised to schedule run times no more frequently than one hour.

 - Recorded Future Domain Risk List
 - Recorded Future Hash Risk List
 - Recorded Future IP Risk List
 - Recorded Future URL Risk List
 - Added new Known Issue regarding the **All** option for the **List to be Retrieved** parameter. If utilizing the **All** option, all other items in the **List to be Retrieved** parameter must be unselected. Attempting to run a feed with the **All** and other items in the list selected will cause the feed to fail.
 - Added a new attribute for the Recorded Future playbook Alerts feed: **Context data**.
 - Added **Target Entities** for related entities in the Recorded Future Alerts feed.
- **Version 2.8.6**
 - Performed optimization improvements for all feeds that contain the Risk List in their name in a effort to reduce the possibility of timeout errors.
- **Version 2.8.5**
 - Resolved a timeout error that was caused by large evidence details.

-
- Removed the following no longer supported lists from Recorded Future Domain Risk List:
 - Historical Malware Analysis DNS Name
 - Recent Malware Analysis DNS Name
 - Added the following new lists to Recorded Future Domain Risk List:
 - Frequently Abused Free DNS Provider
 - Historically Suspected Malware Operation
 - Recently Suspected Malware Operation
 - Recent Cryptocurrency Mining Pool
 - Added the following new lists to Recorded Future IP Risk List
 - Historical Malicious Infrastructure Admin Server
 - Recent Malicious Infrastructure Admin Server
 - Added the following new lists to Recorded Future URL Risk List
 - Historically Suspected Malware Distribution
 - Recently Suspected Malware Distribution
 - Recent Reported C&C URL
 - Historical Reported C&C URL
 - **Version 2.8.4**
 - Commonly updated attributes, such as attributes that involve timestamps and criticality, will now be updated when ingesting new data as opposed to creating duplicate attributes. See the Mapping Tables of each feed for details.
 - **Version 2.8.3**
 - Introduced a results limitation for the **Recorded Future Analyst Note** feed to resolve an offset issue.
 - Added the following new **Topic** configuration options for the **Recorded Future Analyst Note** feed:
 - Geopolitical Intelligence Summary
 - Geopolitical Flash Event
 - Geopolitical Threat Forecast
 - Geopolitical Validated Event
 - Insikt Research Lead

-
- Regular Vendor Vulnerability Disclosures
 - Sigma Rule
 - The Record by Recorded Future
 - Added a new issue to the **Known Issues / Limitations** chapter regarding the API limit for the Analyst Notes and Alerts feeds.
 - **Version 2.8.2**
 - Improved the **Recorded Future Alerts** feed to ingest more information regarding alerts.
 - Added new configuration field for the feed: **Save CVE Data As**.
 - Guide Update - updated Recorded Future Alerts sample response, default mapping table, Related Indicator Type mapping, and added a new Related Indicator Attributes mapping entry.
 - **Version 2.8.1**
 - Updated the Recorded Future Alerts endpoint to API version 3.
 - Removed support from the following problematic lists:
 - Positive Malware Verdict
 - Historical Ransomware Distribution URL
 - Recent Ransomware Distribution URL
 - **Version 2.8.0**
 - The integration now synchronizes Risk lists.
 - **Version 2.7.0**
 - Added a new feed: Recorded Future Playbook Alerts.
 - Added the ability to filter by minimum risk score for the Risk List feeds (Recorded Future Domain Risk List, Recorded Future IP Risk List, Recorded Future URL Risk List, Recorded Future Vulnerability Risk List and Recorded Future Hash Risk List).
 - Added the ability to select the hash types that are ingested by the Recorded Future Hash Risk List, Recorded Future Analyst Note, and Recorded Future Alerts feeds.
 - Added the ability to ingest SHA-1 indicators.
 - **Version 2.6.2**
 - Synchronized the Risk lists for the Risk List feeds to match option updates that Recorded Future performed.

-
- Added time constrained data ingestion for all feeds so manual runs can be performed. Previously, the manual run option was only supported by the Analyst Note feed.
 - **Version 2.6.1**
 - Fixed a parsing error that would occur when no evidence details are provided.
 - **Version 2.6.0**
 - Removed lists from Recorded Future Domain Risk List feed:
 - Ransomware Distribution URL
 - Ransomware Payment DNS Name
 - Removed lists from Recorded Future Vulnerability Risk feed:
 - Observed Exploit/Tool Development in the Wild
 - Historically Observed Exploit/Tool Development in the Wild
 - **Version 2.5.0**
 - Refactored Recorded Future Feeds (aside from Analyst Note).
 - Fixed a bug that caused an Error applying FilterMapping error from the URL Risk List and other similar feeds.
 - Removed lists that are no longer support that would cause the feed to throw a 404 error. Lists removed include:
 - Recorded Future Domain Risk List:
 - C&C URL
 - Recorded Future URL Risk List:
 - C&C
 - Compromised URL
 - Historically Detected Malicious Browser Exploits
 - Recently Detected Malicious Browser Exploits
 - Recently Detected Suspicious Content
 - Historically Detected Suspicious Content
 - Recorded Future Vulnerability Risk List:
 - Recently Observed Exploit/Tool Development in the Wild
 - **Version 2.4.1**
 - Fixed a parsing error with Analyst Note.

-
- **Version 2.4.0**
 - Added Alert details
 - **Version 2.3.0**
 - Added support for MITRE Attack Pattern Sub-Techniques
 - Added 'Save CVE Data As' user configuration parameter for Recorded Future Vulnerability Risk List
 - **Version 2.2.0**
 - Added support to multiple selection for list
 - Fixed issue with MITRE map
 - **Version 2.1.0**
 - Added support for configuration list in the request
 - **Version 2.0.1**
 - Fixed issue with attributes
 - **Version 2.0.0**
 - Added Analyst Note Integration
 - **Version 1.0.0**
 - Initial release